



FÉDÉRATION INTERNATIONALE DE GYMNASTIQUE



FIG Apparatus Norms

CIRQUE DU SOLEIL®



LONGINES®



Official Partners of the FIG

The FIG is proud to present its Official Partners, who not only support the FIG financially and in kind, but understand Gymnastics and the importance of the FIG's efforts to promote the development of all its disciplines.

Our Official Partners help to make our World Championships and the World Gymnaestrada a great success and constantly support our member Federations.

We thank them for their dedication and ask the World of Gymnastics to return the favour by supporting the companies that advance the spirit of Gymnastics.

EUROTRAMP®



GYMNOVA



Janssen
fritsen



AAI®

Chacott

PASTORELLI®



CONTINENTAL

SISAKI®





FÉDÉRATION INTERNATIONALE DE GYMNASTIQUE

Apparatus Norms



↖
K

x x
□
//
oo
3



GYMNOVA
www.gymnova.com

Editorial

In its commitment to serve its partners and performers ever better at the international competition level, the International Federation of Gymnastics (FIG) is exceptionally pleased to introduce the new edition of the *Apparatus Norms* for gymnastics. This publication is based on the revision of the 2015 edition and has been in effect since 1.1.2016.

This document is the result of a team effort led by the members of the FIG Apparatus Commission in close cooperation with the concerned Technical Committees and both the Scientific and Medical Commissions. Mr. Ludwig Schweizer of the University of Freiburg (Germany), Director of the FIG Apparatus Testing Institute has managed the editing process.

The new contents of this FIG Apparatus Manual offer a didactical approach, which allows the readers to learn about the particular functions of each apparatus and about the intricate process that surrounds certification and approval. This publication also serves as a source of official information for all National Federations and lays the foundation of the collaboration between the FIG and the apparatus manufacturers.

The new concept of these regulations' layout makes it possible to update the specific data pertaining to each apparatus used in the various gymnastic disciplines. It allows the technicians, the organizers, and above all the apparatus manufacturers to be kept abreast immediately on the latest developments in this important area. The drafting of these norms has taken into consideration our Technical Regulations, Codes of Points and Media Regulations.

With this publication, the FIG is renewing its commitment to the absolute necessity of providing standards for the apparatus used in official events and to guaranteeing that consistent testing and certification procedures are provided by fully neutral institutes delivering certificates in due form. In this respect, the FIG is pleased to further contribute to the improvement of our gymnasts' safety and to remain vigilant about fair play in competition.

We wish to thank everyone who has contributed to the publication of this document. The FIG wishes to all of them much success and a prosperous future at the service of the gymnasts and their managers.

With our compliments,

INTERNATIONAL FEDERATION OF GYMNASTICS

Bruno Grandi
President

André Gueisbuhler
Secretary General

Wolfgang Willam
*President
Apparatus Commission*

Top equipment made in Holland!

Engineering is a skill which literally **made** Holland. Building windmills, bridges and dams made it possible to claim land from the sea on which many Dutch people live their daily lives. **Attention for detail**, solid **workmanship** and a **design** that is able to withstand the forces of nature over time are basic starting points for any Dutch engineer. It is therefore no wonder that the Gymnastic Equipment, which is designed and built by these very Dutch engineers is known world wide as well for its quality, **durability** and its **suitability** for its purpose.




Foto Erasmus Brug - UN Studie voor Rectorij Amsterdam 2011



**janssen
fritsen**

Janssen-Fritsen Gymnastics b.v.

Phone: +31 492-530930 • export@janssen-fritsen.nl • www.janssen-fritsen.com

Division of chapters

I General part

II Apparatus Norms

III Certificates and diplomas

Appendix

Impressum

IV Testing procedures

Explanations concerning the structure / systematic of the apparatus Norms FIG

Line 1 Number of the chapter
Line 2 Discipline and number of apparatus
Line 3 Date of validity
Line 4 Page number within the chapter

II
MAG 4
01.01.2014
24



FÉDÉRATION INTERNATIONALE DE GYMNASTIQUE

I General Part



Official Supplier

European Championships
Artistic Gymnastics 2011
Berlin

European Championships
Rhythmic Gymnastics 2011
Minsk

World Gymnaestrada
2011
Lausanne



Official partner of FIG / UEG / DTB



SPIETH Gymnastic GmbH

Zeppelinstrasse 126 · D-73730 Esslingen

Telefon ++49 (0)711 / 3 19 71 0

Telefax ++49 (0)711 / 3 19 71 11

Internet: www.spieth-gymnastic.com

E-Mail: info@spieth-gymnastic.com

I
01.01.2009
11

1. Introduction / Layout	
2. Purpose and Principles	I/3
3. Validity of the Apparatus Norms	I/4
4. Guarantee for quality	I/5

TRAMPOLINE-DIVERSITY. Since 1960.

EUROTRAMP®



EUROTRAMP.COM



I
01.01.2014
3

1. Introduction / Layout

The last edition of the Apparatus Norms dates from 2011. Since then, Gymnastics has developed, some Norms have changed, additional testing procedures were introduced and detailed for some apparatus. It was therefore essential that the Apparatus Norms 2011 had to be revised.

The FIG Apparatus Commission has decided to present the new booklet in four parts.

PART I. is the general part and contains the aim of these Rules, the introduction, the layout and general principles.
Part I is aimed at all users.

PART II. contains the actual Apparatus Norms with drawings, measurements, description of functional properties and testing norms.
Part II is also aimed at all users.

PART III. contains the procedures for how to obtain FIG Certificates and Diplomas.
Part III is mainly oriented to the apparatus manufacturers.

PART IV. contains the detailed description of the testing procedures and is directed to the apparatus manufacturers and the FIG recognised Testing Institutes.

2. Purpose and Principles

- The purpose of these Apparatus Norms is first, to have equivalent apparatus at all competitions. It is essential for the competitors to have the same, optimal conditions for the preparations for competitions and at competitions all over the World. This is necessary for practical reasons, for competition fairness and comparison and for safety.
- All apparatus used at official FIG events; the Olympic Games and the World Games must have a valid FIG Certificate. This Certificate will be issued by the FIG, provided the apparatus has been tested successfully.
- The controlled certification by the FIG and the testing procedures guarantee, that the Apparatus Norms are respected. With the Diplomas issued by the FIG, a partnership between the FIG and the apparatus manufacturers is created.

I
01.01.2014
4

- The choice of material and construction must be left to the manufacturers, to allow the apparatus to adapt to progress, development and new construction techniques. Therefore, the FIG only prescribes measurements, functional properties, norms for testing and testing procedures.
- The FIG recognises neutral Testing Institutes, which have to follow the testing procedures decided by the FIG to test the functional properties, the norms and measurements of the apparatus.
- The testing procedures must be constantly developed with the purpose to have meaningful testing procedures for all apparatus and further develop existing procedures. It is important to develop testing procedures which guarantee, that the apparatus fulfil the norms also after intensive use.
- To enforce the Apparatus Norms and to guarantee the quality of apparatus after intensive use, the FIG may, before, during or after an event, control the apparatus and make re-tests at the Testing Institute.
- In case of contradictions between the Apparatus Norms and the Code of Points, the Apparatus Norms prevail.

3. Validity of the Apparatus Norms **FIG Certificate compulsory for all Apparatus**

These Apparatus Norms were decided by the FIG Executive Committee and are valid as of 1st January 2016.

They replace all previous editions as well as all previous decisions and publications regarding apparatus norms from the Executive Committee, Technical Committees and the Apparatus Commission of the FIG.

They are compulsory for all FIG events, as well as at the Olympic Games, World Games, Commonwealth Games, Asian Games, Pan-American Games, University Games and other multi-sport Games with International participation. At all those events, no apparatus which does not have a valid FIG Certificate may be used.

The FIG strongly recommends that at all other national and international events, organised independently by its member federations or unions, only apparatus which have a valid FIG Certificate may be used.

At international events, apparatus without a valid FIG Certificate may only be used provided all participating member federations have agreed in writing and bear the full responsibility and liability for the use of such uncertified apparatus. The FIG waives all responsibility in the cases where apparatus without a valid FIG Certificate are used.

I
01.01.2014
5

4. Guarantee for quality

To guarantee equal quality and fairness for the competitors and to guarantee their safety and health, testing procedures for the quality of apparatus are necessary. Those testing procedures are defined in the Apparatus Norms part II and IV.

These apparatus norms as well as the requested norms and functional properties must not only be fulfilled at the time of the test at the Testing Institute. The apparatus manufacturers must guarantee to produce their apparatus in such a quality that the apparatus also fulfil the requested norms, functional properties and safety aspects after intensive use e.g. after a World Championship.



Innovation for Sports and Wellness.

スポーツと健康の未来を創る

official FIG partner





FÉDÉRATION INTERNATIONALE DE GYMNASTIQUE

II Apparatus Norms

II
01.01.2014
2

	Page
1. Overview of the apparatus of the FIG disciplines	II/5
1.1 MAG Men's artistic gymnastics	
1.2 WAG Women's artistic gymnastics	
1.3 RG Rhythmic gymnastics	
1.4 AER Aerobic gymnastics	
1.5 TRA Trampoline gymnastics	
1.6 ACRO Acrobatic gymnastics	
2. Apparatus for the FIG disciplines, Construction and material description, dimensions	
2.1 MAG Men's artistic gymnastics	II/13
MAG 1 Floor	II/14
MAG 2 Pommel horse	II/16
MAG 3 Rings	II/20
MAG 4 Vaulting table	II/23
MAG 5 Parallel bars	II/29
MAG 6 Horizontal bar	II/32
MAG 11 Landing mat 20 cm	II/35
MAG 12 Landing mat 10 cm (Pommel horse)	II/35
MAG 13 Supplementary mat 10 cm	II/38
MAG 14 Vaulting Board	II/39
MAG 15 Vaulting Board safety collar (Round off vaults)	II/42
MAG 16 Mat for hands (Vault)	II/43
2.2 WAG Women's artistic gymnastics	II/44
WAG 1 Vaulting table	II/45
WAG 2 Uneven bars	II/51
WAG 3 Balance beam	II/54
WAG 4 Floor	II/57
WAG 11 Landing mat 20cm	II/59
WAG 13 Supplementary mat 10cm	II/61
WAG 14 Vaulting Board	II/62
WAG 15 Vaulting Board safety collar (Round off vaults)	II/65
WAG 16 Mat for hands (Vault)	II/66

II
01.01.2014
3

	Page
2.3 RG Rhythmic gymnastics	II/67
RG 1 Performance Area	II/68
RG 2 Rope	II/70
RG 3 Hoop	II/70
RG 4 Ball	II/70
RG 5 Club	II/70
RG 6 Ribbon	II/70
RG 10 Measurement Table	II/73
2.4 TRA Trampoline Gymnastics	II/75
TRA 1 Trampoline	II/76
TRA 2 Double Mini Trampoline	II/81
TRA 3 Tumbling Track	II/86
TRA 11 Landing mat 30cm for DMT, TUM; Safety mat 20cm for TRA, DMT	II/89
TRA 12 Spotter mat for TRA, DMT	II/89
TRA 13 Supplementary mat for TUM	II/90
TRA 14 Vaulting board, Tumbling	II/91
TRA 15 Time measurement device for TRA	II/94
2.5 ACRO Acrobatic Gymnastics	II/98
ACRO 1 Floor	II/99
ACRO 11 Landing mat	II/101
2.6 AER Aerobic Gymnastics	II/102
AER 1 Performance Area	II/103
AER 2 Aerobic Step	II/105
3. Surfaces of apparatus, safety zones, total surfaces	II/108
4. Competition area	II/110
5. Apparatus Control Forms	II/116
6. Required Equipement for FIG – Competition MAG/WAG/RG/TRA	II/121



Foam balance beam
for training
200 cm / 300 cm / 500 cm

QUALITY

with SAFETY
REQUIREMENTS

„I trust in it!“
Elisabeth
Seitz

Elisabeth Seitz
www.elisabeth-seitz.de

YOUR MANUFACTURER FROM THE CENTER OF GERMANY



Bänfer®









II
01.01.2009
5

1 Overview of the apparatus of the FIG disciplines

1 MENS' ARTISTIC GYMNASTICS MAG







II
MAG
01.01.2009
6

Number	Apparatus	Pictogram	Description Construction Material	Test	
				Institute	Competition
APPARATUS					
MAG1	Floor		II MAG1	IV MAG1	yes
MAG2	Pommel horse		II MAG2	IV MAG2	yes
MAG3	Rings		II MAG3	IV MAG3	yes
MAG4	Vaulting table		II MAG4	IV MAG4	yes
MAG5	Parallel bars		II MAG5	IV MAG5	yes
MAG6	Horizontal bar		II MAG6	IV MAG6	yes
SUPPLEMENTARY APPARATUS					
MAG11	Landing mat 20cm		II MAG11	IV MAG11	yes
MAG12	Landing mat 10cm		II MAG12	IV MAG12	yes
MAG13	Supplementary mat 10cm		II MAG13		yes
MAG14	Vaulting board		II MAG14	IV MAG14	yes
MAG15	Vaulting Board safety collar (Round off vaults)		II MAG15		yes
MAG16	Mat for hands (vault)		II MAG16		yes

2 WOMENS'ARTISTIC GYMNASTICS WAG




II
WAG
01.01.2009
7






Number	Apparatus	Pictogram	Description Construction Material	Test	
				Institute	Competition
APPARATUS					
WAG1	Vaulting table		II WAG1	IV WAG1	yes
WAG2	Uneven bars		II WAG2	IV WAG2	yes
WAG3	Balance beam		II WAG3	IV WAG3	yes
WAG4	Floor		II WAG4	IV WAG4	yes
SUPPLEMENTARY APPARATUS					
WAG11	Landing mat 20cm		II WAG11	IV WAG11	yes
WAG13	Supplementary mat 10cm		II WAG13		yes
WAG14	Vaulting board		II WAG14	IV WAG14	yes
WAG15	Vaulting Board safety collar (Round off vaults)		II WAG15		yes
WAG16	Mat for hands (vault)		II WAG16		yes



II
RG
01.01.2011
8

3 RHYTHMIC GYMNASTICS RG

Number	Apparatus	Pictogram	Description Construction Material	Test	
				Institute	Competition
RG1	Floor		II RG1	IV RG1	yes


Number	Apparatus	Pictogram	Description- Construction Material	Test	
				By TC/ par CT	Competition
APPARATUS					
RG2	Rope		II RG2	yes*	yes*
RG3	Hoop		II RG3	yes*	yes*
RG4	Ball		II RG4	yes*	yes*
RG5	Clubs		II RG5	yes*	yes*
RG6	Ribbon		II RG6	yes*	yes*
RG10	Measurement Table with Balance		II RG10	Institute	

* Test with measuring table according to the directives of the competition



II
AER
01.01.2015
9

4 AEROBIC GYMNASTICS AER

Number	Apparatus	Pictogram	Description Construction Material	Test	
				Institute	Competition
APPARATUS					
AER1	Floor		II AER1	IV AER1	Yes
AER2	Aerobic Step		II AER2		Yes

5 TRAMPOLINE GYMNASTICS TRA




II
TRA
01.01.2014
10

Number	Apparatus		Description- Construction Material	Test	
				Institute	Competition
APPARATUS					
TRA1	Trampoline		II TRA1	IV TRA1	yes
TRA2	Double Mini- Trampoline		II TRA2		yes
TRA3	Tumbling track		II TRA3	IV TRA3	yes
SUPPLEMENTARY APPARATUS					
TRA 11	Landing mat 30cm for DMT, TUM; Safety mat for TRA, DMT (20 cm)		II TRA11	IV TRA11	yes
TRA 12	Spotter mat Trampoline Gymnastics DMT		II TRA12		yes
TRA 13	Supplementary mat 10cm for TUM		II TRA13		yes
TRA 14	Vaulting board Tumbling		II TRA14	IV TRA14	yes
TRA 15	Time measurement device for Trampoline competitions (TMD)		II TRA15	IV TRA15	yes

6 ACROBATIC GYMNASTICS ACRO



II
ACRO
01.01.2009
11

Number	Apparatus	Pictogram	Description Construction Material	Test	
				Institute	Competition
APPARATUS					
ACRO1	Floor		II ACRO1	IV ACRO1	yes
SUPPLEMENTARY APPARATUS					
ACRO11	Landing mat 20 cm		II ACRO11	IV ACRO11	yes

II
01.01.2009
12

Advertising 8

II
01.01.2009
13

2 Apparatus of the FIG disciplines Construction and material description, dimensions



2.1 MAG Men's artistic gymnastics

Floor

II
MAG 1
01.01.2014
14

Use • Men's Artistic Gymnastics


Construction / Description of material, measurements

Form	<p>The Performance Area shall have a square format. The surface must be horizontal, even and without gaps. All plates of the under construction within the Performance Area shall have the same arrangement of elastic elements. All elements of the floor have to be connected firmly to prevent slipping.</p> <p>Border: Horizontal and even, at the same height as the Performance area</p> <p>Border's variant : Width 50 cm, horizontal and even, at the same height as the Performance area, additional 50 cm inclination border, slope may not exceed 25 %.</p> <p>Safety zone: The safety zone shall be kept totally free as a surrounding zone around the performance area and the border. It shall be horizontal, even and without gaps.</p>																					
Measurements	<table><tr><td>Performance area</td><td>1200 cm x 1200 cm</td></tr><tr><td></td><td>Tolerance +/- 3 cm</td></tr><tr><td>Diagonals of the performance area:</td><td>1697 cm +/- 5cm</td></tr><tr><td>Border</td><td>100 cm, min.</td></tr><tr><td>Border as a variant</td><td></td></tr><tr><td>Horizontal Area, Width</td><td>50 cm, min.</td></tr><tr><td>Slope max. 25 %, Width</td><td>50 cm, min.</td></tr><tr><td>Height of outer border at the very end</td><td>3,5 cm, max.</td></tr></table> <p>When there is a delimitation strip between the Performance area and the border:</p> <table><tr><td>Delimitation strip width</td><td>5 cm,</td></tr><tr><td></td><td>Tolerance +/- 0,5 cm</td></tr></table> <p>The delimitation strip is part of the Performance area.</p>		Performance area	1200 cm x 1200 cm		Tolerance +/- 3 cm	Diagonals of the performance area:	1697 cm +/- 5cm	Border	100 cm, min.	Border as a variant		Horizontal Area, Width	50 cm, min.	Slope max. 25 %, Width	50 cm, min.	Height of outer border at the very end	3,5 cm, max.	Delimitation strip width	5 cm,		Tolerance +/- 0,5 cm
Performance area	1200 cm x 1200 cm																					
	Tolerance +/- 3 cm																					
Diagonals of the performance area:	1697 cm +/- 5cm																					
Border	100 cm, min.																					
Border as a variant																						
Horizontal Area, Width	50 cm, min.																					
Slope max. 25 %, Width	50 cm, min.																					
Height of outer border at the very end	3,5 cm, max.																					
Delimitation strip width	5 cm,																					
	Tolerance +/- 0,5 cm																					
Functional Properties	<p>Performance area and border</p> <ul style="list-style-type: none">- Equal elasticity on the surface as well as dampening.- When in use it should not have any hindering motion energy- Elasticity and dampening must be balanced in such a way that they guarantee the gymnast stability and freedom of movement. It must not restrict turns and slide movements.- The surface cover of the Performance area must provide a balance between anti-skid and slippage. It must not cause skin burns.- The floor must not produce disturbing sound during the execution of an exercise. It must assure a low noise level.																					
Colours	<p>Of plain colour which choice is left to the manufacturer's discretion. Dark colours are not allowed. For certain events the FIG may stipulate the colours. The delimitation shall have a clear contrast to the performance area.</p>																					

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes: please see chapter IV


Floor

II
MAG 1
01.01.2014
15



- surface de compétition, arena, Wettkampffläche
- cadre, edge, Umrandung
- zone de sécurité, safety zone, Sicherheitszone

variantes, profile - variants, Schnitt - Varianten A, B, C



II
MAG 2
01.01.2017
16

Pommel Horse

Use Men's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of a prismoid body which is placed horizontally onto a base. On the upper surface of the body, two pommels are attached crossways.

The Horse Body:

Its sides - viewed from the two length and two front sides - slant inward.

In cross section the upper surface shows an arch, in length section, it is horizontal, and even, and without gaps, except for the points of attachments.

All corners and edges are rounded.

The profile of the pommel horse's body shall lie within a ± 1 cm pipe at the top and a $\pm 0,5$ cm pipe at the side (red lines) around the specifications (in green) in the draw. The profile of the pommel horse's body shall not include any kinks at the transitions from one radius to another (see draw). The top of the horse's body shall be curved uniformly convex and shall not be flat.

The Pommels:

They are circular in profile, rise from their bases and then make a slight circular transition to the horizontal.

The base which serves as a support conforms to arched upper surface of the horse body.

The Base:

Forms and conception do not have any prescriptions.

It must assure stability of the body and the horizontal position of its length and cross axis; all technical safety rules must be observed.

Measurements

Body :	Length at top	160 cm	Tolerance: * 1 cm/ ¹
	Length at bottom	155 cm	* 1 cm/ ²
	Width at top	35 cm	* 1 cm/ ¹
	Width at bottom	30 cm	* 1 cm/ ²
	Height	28 cm	* 1 cm
	Height from upper surface to the floor:	115 cm	* 1 cm
Pommels:	Inner vertical diameter	≥ 7 cm	
	Width at base	31 cm	* 0,2 cm
	Height	12 cm	* 0,5 cm
	Profile diameter (at the nearly horizontal part)	3,4 cm	* 0,1 cm
	Span of the nearly horizontal part	15 cm	* 0,2 cm

Pommel Horse

Functional Properties

Distance between Pommels:
 Minimum ≤ 40 cm
 Maximum ≥ 45 cm

* refers to the tolerance, +/-,

$/^1$ and $/^2$ are measurements linked to each other. In case of variation, they must move in the same direction, e.g. if width at top is 355 mm, the width at the bottom must be 305 ± 10 mm.

Adjustments :

Pommels The distance between the two pommels, inside measurement, must be continuously adjustable from 40 cm to 45 cm.

Body :

Its support area must be elastic and absorbing.

The side surfaces, as well as corners and edges must have a dampening effect.

Indentations caused by support may not hinder turns of the palms.

The tear proof cover material, which tightly covers the body, may not slip or wrinkle.

The upper surface must offer the ability to glide, but not be slippery.

The cover material must be moisture absorbing and not cause skin burns.

The vertical and cross axis of the horse must be horizontal. During use, the horse must remain static.

Pommels:

In principle, they are made of stiff materials.

A slight flexibility, which must not affect support stability, is provided by the padded upper surface of the body.

The anchoring to the body must assure immobility.

The upper surface is slip proof, but must allow the palms to turn and slide in support.

The pommels must be moisture absorbent and neutral to the use of magnesia.

Base:

It must allow exact levelling of the body, and assure its immobility.

Floor anchoring for stabilization purposes is permitted, as well as anti-skid, dampening floor covering.


II
MAG 2
01.01.2017
18

Pommel Horse

	<p>With exception of parts on the floor (feet) the base may not protrude from the body of the horse. The height of the feet must allow an even, horizontal mat covering.</p> <p>No parts of the base may show sharp corners or edges, nor rough surfaces.</p> <p>Since the body is attached to the base, the stability of the apparatus depends on it as well. This is also one of the most important requirements for safety.</p>
Colours	<ul style="list-style-type: none"> - Are left to the manufacturer's discretion - For certain events the FIG may choose the colour. - Based on practical tests and considered allowed are: - For the body : The natural colour of leather, even when synthetic materials are used for the revetment - For the pommel : Natural wood colour, or a light neutral shade, if synthetic materials are used - For the base : Varnished colour
Mats	<ul style="list-style-type: none"> - The mats used for pommel horse must have a height of 10cm (MAG 11/12)

Pommel Horse

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes: please see chapter IV



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 3
01.01.2015
20

Rings

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of two circular rings, attached to cables suspended on a frame.

The rings have a uniform, circular profile.

The cables have a pivoting mechanism at their suspension point on the frame. In the still position, the cables must hang in the vertical.

The frames consist of two supports and a horizontal beam which contains the attachment devices of the cables.

The frame is held upright by four tension cables, anchored to the floor. (Max. Ø 1 cm).

To distribute the pressure, the supports have widened floor plates.

Measurements

Rings:

Inner diameter

18 cm

* 0,1 cm

Diameter of profile

2,8 cm

* 0,1 cm

Pendulum length below suspension device:

Distance from point of attachment to Lower inner side of the rings

300 cm

* 1 cm

Distance of lower inner side of the rings :

- to floor

280 cm

* 0,5 cm

Straps :

- Length

70 cm

* 1 cm

- Width

4 cm

* 1 cm

Distance between the 2 points of attachment on the frame

50 cm

* 0,5 cm

Frame:

Height of attachment point at horizontal beam:

- to the floor

580 cm

* 1 cm

Inner Distance of supports on the floor

260 cm

min

At height of 320 cm (point of indentation)

280 cm

min

Length of horizontal beam

120 cm

min

Measured 30cm under the attachment point

Distance of tension cables :

- in vertical direction of apparatus

550 cm

* 5 cm

- in cross section to apparatus

400 cm

* 5 cm

* Tolerance, +/-

II
MAG 3
01.01.2015
21

Rings

Functional Properties

The suspension device and the rings must be able to swing out freely in all directions. With the exception, of course, of the cable's direction.

Even submitted to tension, the rings must rotate easily. For this purpose, the pivoting device exists.

Under load both rings shall have the same height above the ground.

The rings must guarantee a sure grip and therefore must not be slippery. The rings must absorb moisture.

The rings as such are made of a stiff material; in effect however, the apparatus must have a certain elasticity, to protect the gymnast's joints. This is done partly through form and the method by which the frame is held, and can be helped by an elastic dampening device on the suspension cables.

This device however may not produce springy or counter swings.

Rings are either made of wood or synthetic material.

Except for sanding, the rings' upper surfaces receive no other treatment. The material must remain natural in order to absorb magnesia and moisture so as to assure a sure grip.

The pivoting mechanism, the elastic dampening device and the stepless height regulator are connected to the hanging points.

The cables are protected by a smooth synthetic cover material.

The straps, to which the rings are attached, are made of leather or of a sturdy equivalent material.

Aside from the required resistance of materials, the stability of the apparatus must be assured.

During the exercise, the frame and the suspension device must not move or cause hindering sways or vibrations.

The required elasticity of the suspension device must not produce springy or counter swings.

Sharp corners and edges and rough surfaces are to be avoided.


The ring cables and fixations must be such that no shortening of the ring cables and straps can occur during the exercises of the gymnasts.

Colour

The rings retain the natural colour of the material.

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

Rings



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 4
01.01.2014
23

Vaulting table

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of a slightly inclined table body which is mounted onto a "monostand" bottom frame. The table body consists of a front surface (A) which, seen from the direction of the vault, is inclined to 8° to the vertical and merges into two arched bends (B1 and B2) and then into a linear cover surface (C) which is inclined 3° to the horizontal. The table body is divided into a bounce area (A) and a push away area (B and C) with a clear colour contrast. The different surfaces merge into each other without any gaps in between. The push away area is slightly rounded in transversal direction (D).

All corners and edges are rounded. The bottom frame must offer the table body a stable and secure supporting surface and must guarantee the abidance by the technical safety regulations. The bottom frame with cushioning may not present any parts that protrude from under the vaulting table's body except on the landing side. As a collision protection dangerous metal parts of the support must be cushioned.

Recommendation: All levers and locking mechanisms should be incorporated into the under construction.

At the landing side the legs of the bottom frame must be cushioned at the same height level as the landing mat (20cm, Tolerance +10cm).

The vaulting table including the cushioning of the bottom frame must represent a "monostand" - construction.

Measurements

Table body:	length:	120 cm	+/- 1 cm
	width:	95 cm	+/- 1 cm

Height at the given measurement point (see drawing)¹: 135 cm +/- 1cm

Upper height at the bounce area (see drawing)¹: 122 cm +/- 1 cm

Remark: For competitions the vaulting table must be positioned on a rigid board which has the same height as the run up area (see below)

)¹: In competitions the apparatus height must correspond to the top level of the run up area.

Maximal orthogonal deviations from the given profile lines in longitudinal and transversal directions: < 1 cm

Protrusion of the leg construction below the table body on the landing side (only allowed with appropriate cut-outs in the landing mat):

15 cm	maximal
-------	---------

Height of the leg frame	8 cm	maximal
-------------------------	------	---------

Circumference of the (cushioned) bottom frame including all levers and fixation devices between the height of 50 cm up to 85 cm

1828mm	maximal
--------	---------

Distance between the (cushioned) leg construction including all levers and fixation devices and the projection of the table body on all four sides between the height of 50 cm up to 85 cm

25 cm	minimal
-------	---------

The adjusted height of the vaulting table must be clearly signed at the side.

II
MAG 4
01.01.2014
24

Vaulting table

Functional Properties

Additional Measurements see drawing. The profile lines towards A, B1, B2 and D are to be respected as indicated in the drawing. Maximum deviations < 1 cm – measured at a right angle to the profile line.

The push away area must be shock-absorbing so that shoulders and wrists are protected.

The rebound properties must be guaranteed to be as homogeneously as possible for all the possible impact points on the table body.

Extended time-shift for rebounding energy at the impact points caused by extreme deflections is not acceptable.

The table body must be evenly cushioned over the entire push away area.

The cover material must be non-slippery but not rough. It may not cause a burning sensation on sliding.

The bounce area must be cushioned with a high-quality material in order to provide a good collision protection.

Recommendation: Any protruding items covered by the cushioning of the stand should be avoided or sufficiently covered to prevent perforation through the cushioning during accidental impact.

In order to avoid swaying, vibrations and shifting, the apparatus must have a device for fastening it to the floor.

Colour

The colour of the surface material may be chosen according to taste. For certain events the colour may be determined by the FIG.

Run up area

The run-up area is composed of a run-up mat and a rigid board underneath the vaulting board.

The run up mat shall be positioned so the carpet threads open in the opposite direction of the gymnast run, offering the greatest friction between the feet and run up mat. The orientation of the run up mat shall be the same in the training halls, warm-up halls, and competition hall.

The start of the run-up (2500 cm) shall be marked by a block, attached at the start of the vault run-up mat

length (measured from the vertical projection of the beginning of the vaulting table, see "reference point" in the drawing,

to the inner side of the block): 2500 + 10 cm

width (run-up mat) 100 +/- 1 cm

width (rigid board underneath) 100cm min

height (same height for run-up mat and board underneath) max 2,5 cm

length of the rigid board underneath the vaulting board 320 +/- 1 cm

The colour of the run-up area must have a clear contrast to the colour of the vaulting board. The whole run up area (run-up mat and the rigid board underneath) shall have the same colour.

II
MAG 4
01.01.2014
25

Vaulting table

Authorized Landing zone

Marking on the supplementary mat above the landing mat (see drawing).
Width of the landing corridor at the table site: 95 cm
Width of the landing corridor (end of 600 cm landing mat): 150 cm
When the authorized landing zone is marked out by stripes:
Marking strip width on the supplementary mat: 5 cm +/-0.5 cm
The marking strip is part of the authorized landing zone.

Additional marking strip width in the centre of the
landing corridor (see drawing): 5 cm +/-0.5 cm


Remarks concerning the drawings:

- Bottom frame construction schematized.
- All dimensions in cm
- Tolerances for all dimensions: +/- 1cm
- Maximal Orthogonal Deviations from the given profiles in longitudinal and transversal directions: <1 cm

Dimensions binding; Construction may be different– drawing as example.

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes: please see chapter IV

Vaulting table





cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 4
01.01.2014
27

Vaulting table




cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 4
01.01.2014
28

Vaulting table



II
MAG 5
01.01.2017
29

Parallel Bars

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of two bars of equal dimensions, which run parallel and at the same height.

The position of the bars is parallel; pre-stressing is allowed.

Each bar is supported by two upright supports, which stand on a stable base frame.

The uprights consist of a static and mobile part, that allow the height and width adjustment of the bars.

In cross section, bars present a drop like profile, which remains unchanged for their entire length.

The profile of the bars shall lie within a $\pm 0,5$ mm pipe around the specifications in the draw. The profile of the bars shall not include any kinks at the transitions from one radius to another (see draw)

Measurements

Bars:

Length	350 cm	* 1 cm
Vertical axis of profile	5 cm	* 0.1cm
Horizontal axis of profile	4 cm	* 0.1cm
Height of upper edge measured from the floor near to the supports	200 cm	* 1 cm
Distance between points of attachment	230 cm	* 1 cm
Distance between bars from	42 cm	
to	52 cm	
Distance between the columns at adjustment levels, min.	48 cm	
Heights of mats	20 cm	* 1 cm

* Tolerance +/-

Width adjustment: continuous adjustment of the distance between bars from at least 42 cm to 52 cm must be possible.

Functional Properties

The bars must have elasticity.

To assure the efficiency of this elasticity the fixing points of the bars on the uprights must be articulated.

No significant swaying of bars in the longitudinal and transversal sense must occur.

The entire apparatus must be stable. Incident vertical and transversal forces must not move the apparatus.


II
MAG 5
01.01.2017
30

Parallel Bars

	<p>The upper surface of the bars must be hygroscopic, and not be slippery.</p> <p>The upper surface of the bars must be made of wood, free of errors (knots, fissure, etc.). Except for sanding, it receives no other treatment.</p> <p>The core may be made of wood or of another material.</p> <p>The rails must be secured against breaking through.</p> <p>The apparatus must not have sharp corners of edges or any protruding parts.</p> <p>Rough surfaces are to be avoided.</p> <p>The adjustment screws must be warranted against unintended adjustments.</p> <p>The adjustment devices must be double locked to assure that they do not cede during use.</p> <p>The base girders as well as the space between them must be covered by mats. They must be even and without gaps and of the same height as the surrounding mats, forming a uniform surface, from which only the uprights rise.</p>
Colours	<p>The rails retain the natural wood colour.</p>


Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes: please see chapter IV

Parallel Bars



vue de côté
side view
Ansicht Längsseite

vue de face
front view
Ansicht Stirnseite



vue de dessus
top view
Aufsicht

détail porte-main
bar detail
Detail Barrenholm

cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maß e bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 6
01.01.2014
32

Horizontal bar

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Form

The Horizontal bar consists of a round bar with a constant diameter, which is held horizontally by two supports.

The supports stand erect on the floor and have additional floor plates for displacing force.

They are held upright by tension cables (Ø max. 1 cm), connected to four floor anchors.

Measurements

Horizontal bar :

Diameter	2,8 cm	* 0.01 cm
Length between attachment points	240 cm	* 1 cm

Distance between the sockets	min	200 cm	* 1 cm
------------------------------	-----	--------	--------

Height of upper edge : - measured from floor	280 cm	* 1 cm
---	--------	--------

The height of the horizontal bar must be adjustable for additional 10 cm to the standard height (280+10 cm * 1 cm).

Height changes at competitions to 280+10 cm must be possible by devices at the supports above the upper surface of the landing mat (20 cm). Wires and chains shall be long enough to increment the height.

Height increases of 10 cm shall be allowed in competitions for gymnasts who touch the mat with their feet during the exercise. This must be announced to the organizers at the time of the nominative entry and verified by the President or a member of the Superior Jury during the training.

Equipment suppliers / Organizers must provide trained staff for a safe, fast and competent height increment if necessary.

Distance of floor anchors :

- Lengthwise	550 cm	* 5 cm
- Crosswise	400 cm	* 5 cm

* Tolerance +/-

Functional Properties

The horizontal Bar must be elastic, and be secured against breaking through.

The elasticity is not just determined by the bar but also by the apparatus, acting as a whole. That is why the placement of the floor anchors, the supports and the tension cables, as well as the degree of tension must be strictly observed to insure uniform elasticity.

The bars attachment to the uprights must be articulated, to assure the effectiveness of its elasticity.

II
MAG 6
01.01.2014
33

Horizontal bar

Colours

The bar must allow turn and glide movements without slipping.

The apparatus must be stable. The supports must not move or sway during use.

Neither the bar nor the tension cables should produce disturbing sounds during use.


Preferably such materials should be used which guarantee a slim form and should not block the view.

The bar retains the colour of natural polished steel.

Colours or designs of the remaining parts are left to the discretion of the manufacturer. The FIG may designate the colour for specific events.

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

Horizontal bar



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 11/12
01.01.2009
35

Landing mats

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Form	<p>Their upper surface must be horizontal, even and without gaps.</p> <p>Specially designed mats must be used to cover the basis of the apparatus evenly.</p>
Measurements	<p>Height of the landing mats (MAG 3, 4, 5, 6): 20 cm * 1 cm</p> <p>Height of the landing mats pommel horse (MAG 2): 10 cm * 1 cm</p> <p>* Tolerance +/-</p> <p>lengths and widths see drawing</p>
Functional Properties	<p>Absorbency : Mats must absorb motion energy in order to reduce the reaction transmitted to the body of the landing gymnast to a tolerable proportion.</p> <p>They must respond to increased penetration with an evenly increasing resistance.</p> <p>Stability and Freedom of Movement : Absorbency of the mats must be balanced in order to guarantee standing, walking stability and freedom of movement.</p> <p>Indentations caused by the incidence of compressive forces must not encase the body parts, thereby hindering freedom of movements. They may not be too deep or narrow.</p> <p>If a cover is used, such cover may not plaid and create hindering folds. The mats' upper surface material must offer a balance between anti-slip and slippage. It should be neither slippery nor possess inhibiting resistance.</p> <p>By no means should mats be dislocated during performances. An anti-skid cover on the mats' underside may provide this condition.</p> <p>The border zones of the mats which are pushed together should practically have the same functional properties as the remaining surface. Impacts on the border zones should not cause different indentations than on the remaining surface. For this purpose, and to bridge joints, continuous runners are permitted.</p>

II
MAG 11/12
01.01.2009
36

Landing mats

Colour

Preference should be given to uniform colours.

The upper surface must not show optically disturbing patterns or insignia.

The FIG may designate the colour for certain events.


Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
MAG 11/12
01.01.2009
37


Landing mats

cotes minimales en cm, minimum dimensions in cm, minimale Maße in cm


MAG 2
cheval d'arçons
pommel horse
Pauschenpferd




MAG 3
anneaux
rings
Ringe




MAG 4
saut
vault
Sprung



MAG 5
barres parallèles
parallel bars
Barren



MAG 6
barre fixe
horizontal bar
Reck



II
MAG 13
01.01.2016
38

Supplementary mats

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Use	The use of a supplementary mat is compulsory for the athletes on the vault and on Horizontal bar.
Form	Their upper surface must be horizontal, even and without gaps. The supplementary mats have to be laid on the landing mats (MAG11). At the vault the supplementary mat shall be attached (i.e. using Velcro).
Measurements	<p>Height of the supplementary mats: 10 cm * 1 cm</p> <p>Vault (MAG4): 600 x 200 cm * 1 cm</p> <p>Horizontal bar (MAG6, at both sides): 400 x 200 cm * 1 cm</p> <p>* Tolerance +/-</p> <p>For the marking of the landing zone see MAG4.</p>
Functional Properties	<p>The foam of the supplementary mats shall have a density of 25 kg / m³ (+/- 2,5 kg /m³). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be ≥ 115 kPa, the compression stress value 40% shall be 4,0 (+/- 1,0) kPa (ISO 3386-1 – Amd1: 2010).</p> <p>By no means should mats be dislocated during performances. At the vault the supplementary mat shall be attached to the landing mat.</p>
Colour	<p>Preference should be given to uniform colours.</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour for certain events.</p>

II
MAG 14
01.01.2016
39

Vaulting board

- Use
- Men's Artistic Gymnastics
 - Vault (MAG4) – “hard” and “soft”
 - Parallel bars (MAG5) – “soft”

Construction / Description of material, measurements

Form

The profile of the vaulting board must adhere exactly to the respective blue print.

Its upper surface rises in an arched form, approaching the horizontal between 75 cm and 95 cm, measured from the frontal angle. The height reached at this point, may not be exceeded. After this point, the upper surface may continue horizontally or slope downward.

The rise of the arch is 3.5 cm +/- 0,5 cm.

For competitions a “soft” and a “hard” vaulting board shall be available. The “hard” board shall be marked with a dot on the surface.

Measurements

- Length	120 cm	* 1 cm
- Width	60 cm	* 1 cm
- Height	20 cm	* 1 cm
- Height (run-up side)	max 3 cm	
- Cushion Cover	2 cm	* 0,5 cm
- Total height with cushion cover	22 cm	* 1,5 cm
- Free space between floor and the lower edge of the vaulting board at the run-up side	max. 1 cm	

*Tolerance +/-

The stipulated length and height refers to the vertical projection of the upper plate, i.e. the take-off plate.

The base may be larger, but cannot extend more than 2 cm beyond the projection of the board.

Labelling of the “hard” vaulting board on the surface by a dot with clear contrast on the longitudinal midline:

Distance to the side of run up	5 cm
Diameter	8 cm

Functional Properties

The functional properties of the vaulting board (hardness, damping, elasticity) shall not be adjustable (i.e. springs must be fixed so that they cannot be easily removed by hand).

The elasticity of the vaulting board must be most effective in the area between 75 cm and 95 cm, measured horizontally from the frontal angle.

The vaulting-board must dampen the counter pressure, i.e. reduce motion energy.

Elasticity and absorbency must be evenly distributed, so that the effect of the vaulting board differs only slightly, regardless whether the force of the impact is at the middle axis, or away from it.


The upper surface of the vaulting board must offer slip resistance.

II
MAG 14
01.01.2016
40

Vaulting board

	<p>The vaulting board must not produce disturbing sounds during its use.</p> <p>The board shall not slide at the time of impact of the athlete. This shall be achieved by anti-slip devices at the bottom side of the board or at the board underneath the vaulting board. The slip resistance shall be provided especially when the board bottoms out at the middle part.</p> <p>The vaulting board and its base may not have any sharp corners, edges and no protruding parts. Mainly the upper and under edge of the upper part of the Vaulting board towards the apparatus side (Vaulting Table, Balance Beam of Uneven Parallel Bars) shall be cushioned and rounded.</p>
Colour	<p>The choice of colour is left to the discretion of the manufacturer.</p> <p>With exception of the dot for "hard" vaulting boards optically disturbing patterns, stripes or insignia on the upper surface are not permitted.</p> <p>The FIG may designate the colour for certain events.</p>
<p>Norms / Functional properties Regarding tests carried out by FIG Tests Institutes : please see chapter IV</p>	

Vaulting board



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
MAG 15
01.01.2015
42

Vaulting Board safety collar (Round off vaults)

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Use	The usage of the safety collar around the vaulting board is compulsory for round-off entries at the vault. It is not allowed to place the safety collar on the foot of the vaulting table or underneath the vaulting table.
Form	<p>The safety collar is "u-shaped" and surrounds the vaulting board at the sides and the front toward the vaulting table. At the sides of the vaulting board its upper surface rises in an arched form in the same level as the vaulting board. At the front side of the vaulting board the surface of the safety collar is horizontal and even.</p> <p>The whole surface of the safety collar and the corresponding surface of the vaulting board need to be of the same height level..</p>
Measurements	<p>Overall length: 120 cm (± 1 cm)</p> <p>Minimal width at the side of the vaulting board: 20 cm</p> <p>Length at the front part of the vaulting board: 20 cm ($\pm 0,5$ cm)</p> <p>Maximal Difference between the height of the safety collars' and the boards' surface (respecting the arched form): ± 1 cm</p> <p>Maximal gap between the safety collar and the vaulting board on all three sides: 0,5 cm</p>
Functional Properties	<p>The safety collar has to provide a safe area around the vaulting board in case of an athlete misses the board for a take-off towards the vaulting table, therefore the safety collar must provide sufficient stability and cushioning at the whole upper surface. The bottom side shall have an "anti-slip" surface (i.e. Velcro) to prevent the safety collar from slipping away.</p> <p>The safety collar shall not hinder the vaulting board in its functional properties neither by restricting the airflow during the compression of the vaulting board nor hindering the movement of the upper parts during foot contact.</p>
Colour	<p>The upper surface must not show optically disturbing patterns or insignia. The colour must be uniform and in contrast to the vaulting board. The FIG may designate the colour for certain events.</p>

II
MAG 16
1.01.2009
43

Mat for Hands (Vault)

Use • Men's Artistic Gymnastics

Construction / Description of material, measurements

Use	A mat for hands can be used by the athletes for round-off entries on the vault		
Form	The upper surface must be horizontal and even. The mat for hands can be laid on the run-up area to cushion the hand contact during round-off entries onto the vaulting board.		
Measurements	Length in direction of the run-up:	120 cm	* +10 cm
	Width:	100 cm	* ±1 cm
	Height of the mat for hands:	3 cm	*±0,5 cm
	* Tolerance		
Functional Properties	<p>The cover material must be non-slippery but not rough. It may not cause a burning sensation. If a cover is used, such cover may not be bulged and create hindering folds.</p> <p>The bottom side shall have an "anti-slip" surface (i.e. Velcro) to prevent the mat for hands from slipping away.</p>		
Colour	<p>The upper surface must not show optically disturbing patterns or insignia. The colour must be uniform and in contrast to the run-up area.</p> <p>The FIG may designate the colour for certain events.</p>		

II
WAG
01.01.2014
44



2.2 WAG Women's artistic gymnastics

II
WAG 1
01.01.2014
45

Vaulting Table

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Form	<p>The apparatus consists of a slightly inclined table body which is mounted onto a “monostand” bottom frame. The table body consists of a front surface (A) which, seen from the direction of the vault, is inclined to 8° to the vertical and merges into two arched bends (B1 and B2) and then into a linear cover surface (C) which is inclined 3° to the horizontal. The table body is divided into a bounce area (A) and a push away area (B and C) with a clear colour contrast. The different surfaces merge into each other without any gaps in between. The push away area is slightly rounded in transversal direction (D). All corners and edges are rounded. The bottom frame must offer the table body a stable and secure supporting surface and must guarantee the abidance by the technical safety regulations. The bottom frame with cushioning may not present any parts that protrude from under the vaulting table's body except on the landing side. As a collision protection dangerous metal parts of the support must be cushioned.</p> <p>Recommendation: All levers and locking mechanisms should be incorporated into the under construction.</p> <p>At the landing side the legs of the bottom frame must be cushioned at the same height level as the landing mat (20cm, Tolerance +10cm).</p> <p>The vaulting table including the cushioning of the bottom frame must represent a “monostand” - construction.</p>			
Measurements	Table body:	length:	120 cm	+/- 1 cm
		width:	95 cm	+/- 1 cm
	Height at the given measurement point (see drawing)) ¹ :			125 cm +/-1 cm
	Upper height at the bounce area (see drawing)) ¹ :			112 cm +/- 1 cm
	Remark: For competitions the vaulting table must be positioned on a rigid board which has the same height as the run up area (see below).) ¹ : In competitions the apparatus height must correspond to the top level of the run up area.			
	Maximal orthogonal deviations from the given profile lines in longitudinal and transversal directions:			
				< 1 cm
	Protrusion of the leg construction below the table body on the landing side (only allowed with appropriate cut-outs in the landing mat):			
				15 cm maximal
	Height of the leg frame			8 cm maximal
Circumference of the (cushioned) bottom frame including all levers and fixation devices between the height of 50 cm up to 85 cm			182,8cm maximal	
Distance between the (cushioned) leg construction including all levers and fixation devices and the projection of the table body on all four sides between the height of 50 cm up to 85 cm			25 cm minimal	
The adjusted height of the vaulting table must be clearly signed at the side.				

II
WAG 1
01.01.2014
46

Vaulting Table

Functional Properties

Additional Measurements see drawing. The profile lines towards A, B1, B2 and D are to be respected as indicated in the drawing. Maximum deviations < 1 cm – measured at a right angle to the profile line.

The push away area must be shock-absorbing so that shoulders and wrists are protected.

The rebound properties must be guaranteed to be as homogeneously as possible for all the possible impact points on the table body.

Extended time-shift for rebounding energy at the impact points caused by extreme deflections is not acceptable.

The table body must be evenly cushioned over the entire push away area. The cover material must be non-slippery but not rough. It may not cause a burning sensation on sliding.

The bounce area must be cushioned with a high-quality material in order to provide a good collision protection.

Recommendation: Any protruding items covered by the cushioning of the stand should be avoided or sufficiently covered to prevent perforation through the cushioning during accidental impact.

In order to avoid swaying, vibrations and shifting, the apparatus must have a device for fastening it to the floor

Colour

The colour of the surface material may be chosen according to taste. For certain events the colour may be determined by the FIG.

Run up area

The run-up area is composed of a run-up mat and a rigid board underneath the vaulting board.

The run up mat shall be positioned so the carpet threads open in the opposite direction of the gymnast run, offering the greatest friction between the feet and run up mat. The orientation of the run up mat shall be the same in the training halls, warm-up halls, and competition hall.

The start of the run-up (2500 cm) shall be marked by a block, attached at the start of the vault run-up mat.

length (measured from the vertical projection of the beginning of the vaulting table, see "reference point" in the drawing,

to the inner side of the block) 2500 + 10 cm

width (run-up mat) 100 cm +/- 1 cm

width (rigid board underneath) 100 cm min.

height (same height for run-up mat and board underneath) max 2,5 cm

length of the rigid board underneath the vaulting board 320 cm +/- 1 cm

The colour of the run-up area must have a clear contrast to the colour of the vaulting board. The whole run up area (run-up mat and the rigid board underneath) shall have the same colour.

II
WAG 1
01.01.2014
47

Vaulting Table

Authorized Landing zone

Marking on the supplementary mat above the landing mat (see drawing).
 Width of the landing corridor at the table site: 95 cm
 Width of the landing corridor (end of 600 cm landing mat): 150 cm
 When the authorized landing zone is marked out by stripes:
 Marking strip width on the supplementary mat 5 cm +/-0.5 cm
 The marking strip is part of the authorized landing zone.
 Additional marking strip width in the centre of the
 landing corridor (see drawing): 5 cm +/-0.5 cm

Remarks concerning the drawings:


- Bottom frame construction schematized.
- All dimensions in cm
- Tolerances for all dimensions: +/- 1cm
- Maximal Orthogonal Deviations from the given profiles in longitudinal and transversal directions: <1 cm

Dimensions binding; Construction may be different– drawing as example.

Norms / Functional properties
 Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
WAG 1
01.01.2014
48

Vaulting Table





cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
WAG 1
01.01.2014
49

Vaulting Table




cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
WAG 1
01.01.2014
50

Vaulting Table



II
WAG 2
01.01.2015
51

Uneven Bars

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of two bars, which run parallel, but at different heights, and are carried by a support base.

The support base has four uprights, which are held by tension cables (Ø max 1 cm) anchored to the floor.

Each bar is carried by 2 supports.

One low and one high support are connected to a floor device and a width adjustment device.

Measurements

Bars :

Diameter	4,0 cm	* 0,1 cm
Length	240 cm	* 1,0 cm
Distance between the sockets	min 200 cm	* 1,0 cm

Height of the upper edge of the bars in inner diagonal position 180 cm:

upper bar (to the floor)	250 cm	* 1,0 cm
lower bar (to the floor)	170 cm	* 1,0 cm

Inner diagonal distance (see drawing) between the 2 bars adjustable from min 130 - 180 cm max * 1,0 cm

The diagonal distance must be adjustable continuously or with increments of max 2 cm.

The diagonal distance (expressed in cm) must be shown on a scale at the distance adjustment device.

The height of the bars must be adjustable for additional 10 cm to the standard height (lower bar: 170+10 cm; upper bar: 250+10 cm *1 cm).

At the increased height the inner diagonal distance between the bars shall be not more than 182 max* 1,0 cm

Height increases of 10 cm shall be allowed in competitions for gymnasts who touch the mat with their feet during the exercise. This must be announced to the organizers at the time of the nominative entry and verified by the President or a member of the Superior Jury during the training.

Equipment suppliers / Organizers must provide trained staff for a safe, fast and competent height increment if necessary.

Transition periods for different technical solutions and maximal inner diagonal distances between the bars for 10 cm height increase to the standard height, upon request of taller athletes only:

Transition Period	10 cm Height Adaption by	Maximal inner diagonal Distance between Bars (cm)
Until 2016-12-31	a) 10 cm Blocks underneath the base)* b) 10 cm height increase at the stands)*	180
From 2017-01-01 to 2019-12-31	a) 10 cm Blocks underneath the base)* b) 10 cm height increase at the stands)*	182 ± 1
From 2020-01-01	10 cm height increase at the stands)*	182 ± 1

)* : provided that this technical solution is homologated by passed FIG standardization tests.

II
WAG 2
01.01.2015
52

Uneven Bars

Functional Properties	Distance of floor anchors : lengthwise 550 cm * 5 cm crosswise 400 cm * 5 cm
	<p>Both bars must have the same, uniform elasticity. To assure this, their supports must be articulated.</p> <p>The bar surface must provide a good glide and turn capability but may not be slippery.</p> <p>To ensure grip stability, the bars' surface must absorb moisture.</p> <p>The bars must be secured (reinforced) against breaking through.</p> <p>A safeguard system must prevent an unintended release of the movable components of the apparatus.</p>
Colour	<p>When the apparatus is used for performances, no hindering sways or vibrations and counter swings should occur.</p> <p>The bars retain the natural colour of wood. They are neither lacquered, nor polished.</p>

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
WAG 3
01.01.2011
54

Balance Beam

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Form

The apparatus consists of a beam, which is held by a base consisting of 2 supports.

Lengthwise, the beam shall be straight and its upper surface and axis shall be even and horizontal.

Viewed in cross section, the sides of the beam are arched.

The base design is not prescribed.

However, its legs may not protrude beyond the projection of the beam in its longitudinal direction. The supports of the beam must be cushioned. The cushioned parts shall not protrude the vertical projection of the beam.

The front parts of the beam must be cushioned by rounded, damping padding. The padding must reach the top edge of the beam, but the radius of the rounding must begin immediately at the end of the beam to guarantee that the padding does not prolong the total length of the beam (examples see drawing)

Measurements

Beam :

Length	500 cm	* 1 cm
Cross section: - Upper surface	10 cm	* 0,5 cm
- Horizontal axis	13 cm	* 0,5 cm
- Vertical axis	16 cm	* 0,5 cm
- Bottom surface	10 cm	* 0,5 cm

Height of upper surface measured from the floor	125 cm	* 1 cm
---	--------	--------

Legs of base:

Distance	max. 500 cm
Width	max. 125 cm

Cushioning of the supports:

Thickness	min. 15 mm
Width of the supports incl. cushioning	max. 13 cm

Cushioning of the front parts of the beam:

Thickness	min. 15 mm up to max. 30 mm
-----------	-----------------------------

The Beam might have a height adjustment. It can be continuous or in 5 cm increments. However, the prescribed height of 125 cm * 1cm shall be observed at competition site.

Continuous height adjustment is recommended for levelling purposes.

II
WAG 3
01.01.2011
55

Balance Beam

Functional Properties

The surface must have impact absorbent characteristics to protect the gymnast's joints and limbs. It should also have elasticity to support the jumps.

One of the most important properties of the beam is that it must be step safe. Elasticity must be equally distributed and must not disturb a sure step.

The upper surface material of the beam must permit effortless gliding and turning, but not be slippery.

The front parts of the beam must be padded.

The cover material must not produce skin burns.

The upper edge of the padding at the front parts of the beam shall not be harder than the surface of the beam.

All protruding parts, especially screws underneath the balance beam shall be cushioned or hidden.

During an exercise, the beam may not move, topple or sway.


Colour

The colour of the beam must distinctly differ from the colour of the mats.


Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
WAG 3
01.01.2011
56


Balance Beam



vue de côté
side view
Ansicht Längsseite




vue de face
front view
Ansicht Stirnseite




vue de dessus
top view
Aufsicht

coupe longitudinale
beam end, longitudinal
Längsschnitt Balkenkopf



coupe transversale
de la poutre
beam, cross-section
Balken-Querschnitt



Variante

cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
WAG 4
01.01.2014
57

Floor

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Form	<p>The Performance Area shall have a square format. The surface must be horizontal, even and without gaps. All plates of the underconstruction within the Performance Area shall have the same arrangement of elastic elements. All elements of the floor have to be connected firmly to prevent slipping.</p> <p>Border: Horizontal and even, at the same height as the surrounding performance area.</p> <p>Border, variation : Width 50 cm, horizontal and even, at the same height as the performance area, additional 50 cm inclination border, slope may not exceed 25 %.</p> <p>Safety zone: The safety zone shall be kept totally free as a surrounding zone around the performance area and the border. It shall be horizontal, even and without gaps.</p>		
Measurements	Performance area	1200 cm x 1200 cm	
		Tolerance +/- 3 cm	
	Diagonals of the performance area:	1697 cm	+/- 5cm
	Border	100 cm,	min.
	Border as a variant		
	Horizontal part, width	50 cm,	min.
	Slope max. 25 %, width	50 cm,	min.
	Height of outer border	3,5 cm,	max.
	When there is an delimitation strip between the performance area and the border:		
	Width of the delimitation strip	5 cm	+/- 0,5 cm
	The delimitation strip is part of the performance area.		
Functional Properties	<p>Performance area and border :</p> <ul style="list-style-type: none"> - Equal elasticity and absorbency. - While in use, no counter swings must be produced. - Elasticity and absorbency of the floor must be balanced in such a way, that they guarantee the gymnast stability and freedom of movement. They must not restrict turns and slide movements. - The surface cover of the performance area must provide a balance between anti-skid and slippage. It must not cause skin burns. - The floor must not produce disturbing sounds. It must assure a low noise level. 		
Colour	<p>Plain colour, left to the discretion of the manufacturer. Dark colours are not allowed. For certain events the FIG may stipulate the colour. The delimitation shall have a clear contrast to the performance area.</p>		

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
WAG 11
27.03.2008
59

Landing Mats

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Form	<p>Their upper surface must be horizontal, even and without gaps.</p> <p>Specially designed mats must be used to cover the basis of the apparatus evenly.</p>
Measurements	<p>Height of landing mats (WAG1, WAG2, WAG3): 20 cm +/- 1 cm</p> <p>Width and length see drawing</p>
Functional Properties	<p>Absorbency: The mats must absorb motion energy, in order to reduce the reaction transmitted to the body of the landing gymnast, to a tolerable proportion.</p> <p>They must respond to increased penetration with an evenly increasing resistance.</p> <p>Stability and Freedom of Movement : Absorbency of the mats must be balanced in order to guarantee standing, walking stability and freedom of movement, there must be an equal balance between elasticity and absorbency properties.</p> <p>Indentations caused by the incidence of compressive forces must not encase the body parts, thereby hindering freedom of movements mainly of rolling a part of the body.</p> <p>If a cover is used, such cover may not cause hindering folds. The mats' upper surface material must offer a balance between anti-slip and slippage. It must be neither slippery nor possess inhibitory resistance.</p> <p>By no means should mats be dislocated during performances. An anti-skid cover on the mats' underside may provide this condition.</p> <p>The border zones of the mats which are pushed together should practically have the same functional properties as the remaining surface. Impacts on the border zones should not cause different indentations than on the remaining surface. For this purpose, and to bridge joints, continuous runners are permitted.</p>
Colour	<p>Preference should be given to uniform colours.</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour of certain events.</p>

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV


II
WAG 11
27.03.2008
60

Landing Mats

cotes minimales en cm, minimum dimensions in cm, minimale Maße in cm


WAG 1

saut
vault
Sprung




WAG 3

barres asymétriques
uneven bars
Stufenbarren



WAG 2

poutre
beam
Balken



II
WAG 13
01.01.2015
61

Supplementary Mats

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Use	The usage is compulsory for the athletes at Uneven Bars, Balance Beam and at the vault.
Form	Their upper surface must be horizontal, even and without gaps. The supplementary mats have to be laid on the landing mats (WAG11). At the vault the supplementary mat shall be attached (i.e. using Velcro).
Measurements	<p>Height of the supplementary mats: 10 cm * 1 cm</p> <p>Vault (WAG1): 600 x 200 cm * 1 cm</p> <p>Uneven bars, balance beam (WAG2, WAG 3): 400 x 200 cm * 1 cm</p> <p>* Tolerance +/-</p> <p>For the marking of the landing zone see WAG1.</p>
Functional Properties	<p>The foam of the supplementary mats shall have a density of 25 kg / m³ (+/- 2,5 kg /m³). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be ≥ 115 kPa, the compression stress value 40% shall be 4,0 (+/- 1,0) kPa (ISO 3386-1 – Amd1: 2010)</p> <p>By no means should mats be dislocated during performances. At the vault the supplementary mat shall be attached to the landing mat</p>
Colour	<p>Preference should be given to uniform colours.</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour for certain events.</p>

II
WAG 14
01.01.2016
62

Vaulting Board

- | | |
|-----|--|
| Use | <ul style="list-style-type: none"> • Women's Artistic Gymnastics <ul style="list-style-type: none"> - Vault (WAG1) – “hard” and “soft” - Uneven bars (WAG2) – “soft” - Balance beam (WAG3) – “soft” |
|-----|--|

Construction / Description of material, measurements

Form

The profile of the vaulting board must adhere exactly to the respective blue print.

Its upper surface rises in an arched form, approaching the horizontal between 75 cm and 95 cm, measured from the frontal angle. The height reached at this point, may not be exceeded. After this point, the upper surface may continue horizontally or slope downward.

The rise of the arch is 3.5 cm +/- 0,5 cm.

For competitions a “soft” and a “hard” vaulting board shall be available. The “hard” board shall be marked with a dot on the surface.

Measurements

- Length	120 cm	* 1 cm
- Width	60 cm	* 1 cm
- Height	20 cm	* 1 cm
- Height (run-up side)	max 3 cm	
- Cushion Cover	2 cm	* 0,5 cm
- Total height with cushion cover	22 cm	* 1,5 cm
- Free space between floor and the lower edge of the vaulting board at the run-up side	max. 1 cm	

*Tolerance +/-

The stipulated length and height refers to the vertical projection of the upper plate, i.e. the take-off plate.

The base may be larger, but cannot extend more than 2 cm beyond the projection of the board.

Labelling of the “hard” vaulting board on the surface by a dot with clear contrast on the longitudinal midline:

Distance to the side of run up	5 cm
Diameter	8 cm

Functional Properties

The functional properties of the vaulting board (hardness, damping, elasticity) shall not be adjustable (i.e. springs must be fixed so that they cannot be easily removed by hand).

The elasticity of the vaulting board must be most effective in the area between 75 cm and 95 cm, measured horizontally from the frontal angle.

The vaulting-board must dampen the counter pressure, i.e. reduce motion energy.

Elasticity and absorbency must be evenly distributed, so that the effect of the vaulting board differs only slightly, regardless whether the force of the impact is at the middle axis, or away from it.

II
WAG 14
01.01.2016
63

Vaulting Board

Colour

The upper surface of the vaulting board must offer slip resistance.

The vaulting board must not produce disturbing sounds during its use.

The board shall not slide at the time of impact of the athlete. This shall be achieved by anti-slip devices at the bottom side of the board or at the board underneath the vaulting board. The slip resistance shall be provided especially when the board bottoms out at the middle part.


The vaulting board and its base may not have any sharp corners, edges and no protruding parts. Mainly the upper and under edge of the upper part of the Vaulting board towards the apparatus side (Vaulting Table, Balance Beam or Uneven Parallel Bars) shall be cushioned and rounded.

The choice of colour is left to the discretion of the manufacturer.

With exception of the dot for "hard" vaulting boards optically disturbing patterns, stripes or insignia on the upper surface are not permitted.

The FIG may designate the colour for certain events.

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
WAG 15
01.01.2015
65

Vaulting Board safety collar (Round off vaults)

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Use	The usage of the safety collar around the vaulting board is compulsory for round-off entries at the vault. It is not allowed to place the safety collar on the foot of the vaulting table or underneath the vaulting table.
Form	<p>The safety collar is "u-shaped" and surrounds the vaulting board at the sides and the front toward the vaulting table. At the sides of the vaulting board its upper surface rises in an arched form in the same level as the vaulting board. At the front side of the vaulting board the surface of the safety collar is horizontal and even.</p> <p>The whole surface of the safety collar and the corresponding surface of the vaulting board need to be of the same height level..</p>
Measurements	<p>Overall length: 120 cm (± 1 cm)</p> <p>Minimal width at the side of the vaulting board: 20 cm</p> <p>Length at the front part of the vaulting board: 20 cm ($\pm 0,5$ cm)</p> <p>Maximal Difference between the height of the safety collars' and the boards' surface (respecting the arched form): ± 1 cm</p> <p>Maximal gap between the safety collar and the vaulting board on all three sides: 0,5 cm</p>
Functional Properties	<p>The safety collar has to provide a safe area around the vaulting board in case of an athlete misses the board for a take-off towards the vaulting table, therefore the safety collar must provide sufficient stability and cushioning at the whole upper surface. The bottom side shall have an "anti-slip" surface (i.e. Velcro) to prevent the safety collar from slipping away.</p> <p>The safety collar shall not hinder the vaulting board in its functional properties neither by restricting the airflow during the compression of the vaulting board nor hindering the movement of the upper parts during foot contact.</p>
Colour	<p>The upper surface must not show optically disturbing patterns or insignia. The colour must be uniform and in contrast to the vaulting board. The FIG may designate the colour for certain events.</p>

II
WAG 16
01.01.2009
66

Mat for Hands (Vault)

Use • Women's Artistic Gymnastics

Construction / Description of material, measurements

Use	A mat for hands can be used by the athletes for round-off entries on the vault		
Form	The upper surface must be horizontal and even. The mat for hands can be laid on the run-up area to cushion the hand contact during round-off entries onto the vaulting board.		
Measurements	Length in direction of the run-up:	120 cm	* +10 cm
	Width:	100 cm	* ±1 cm
	Height of the mat for hands:	3 cm	* ±0,5 cm
	* Tolerance		
Functional Properties	<p>The cover material must be non-slippery but not rough. It may not cause a burning sensation. If a cover is used, such cover may not be bulged and create hindering folds.</p> <p>The bottom side shall have an "anti-slip" surface (i.e. Velcro) to prevent the mat for hands from slipping away.</p>		
Colour	<p>The upper surface must not show optically disturbing patterns or insignia. The colour must be uniform and in contrast to the run-up area.</p> <p>The FIG may designate the colour for certain events.</p>		

II
RG
01.01.2014
67



2.3 RG Rhythmic gymnastics

TOGETHER WE CREATE



YANA KUDRYAVTSEVA WITH VENTURELLI RIBBON ART. 616



OFFICIAL PARTNER OF



II
RG 1
01.01.2015
68

Performance Area

Use • Rhythmic Gymnastics

Construction / Description of material, measurements

Form

The Performance Area shall have a square format. The surface must be horizontal, even and without gaps.
 Border :
 Horizontal, even, and at the same height as the performance area.
 Safety zone:
 The safety zone shall be kept totally free as a surrounding zone around the performance area and the border. It shall be horizontal, even and without gaps.
 Direction of carpet seams:
 If the surface is composed of several parallel carpet rolls, the seams shall be perpendicular to the direction of the judges' tables.
 The performance area shall be composed by a damping under – construction and an overlying carpet.

Measurements

Performance area	1300 x 1300 cm
Tolerance +/- 3 cm	
Diagonals of the performance area:	1838 cm +/- 5cm
Border (25 + 25)	50 cm
Safety border	200 cm
Border as a variant	
Horizontal Area, Width	25 cm
Slope max. 20 %, Width	25 cm

When there is a delimitation strip between the performance area and the border:
 Width of the delimitation strip 5 cm +/- 0,5 cm
 The delimitation strip is part of the performance area.

Performance area and border :

- Equal elasticity on the surface as well as dampening.
- When in use it should not have any motion energy.
- Elasticity and dampening must be balanced in such a way that they guarantee the gymnast stability and freedom of movement. It must not restrict turns and slide movements.
- The surface cover of the performance area must provide a balance between anti-skid and slippage. It must not cause skin burns.
- The performance area must not produce disturbing sound during the execution of an exercise. It must assure a low noise level.


Colour

Of plain colour which choice is left to the manufacturer's discretion. Dark colours are not allowed. For certain events the FIG may stipulate the colours. The delimitation shall have a clear contrast to the performance area.

Norms / Functional properties
 Regarding tests carried out by FIG Tests Institutes : please see chapter IV


II
RG 1
01.01.2015
69

Performance Area



- surface de compétition, arena, Wettkampffläche
- cadre, edge, Umrandung
- zone de sécurité, safety zone, Sicherheitszone

variantes, profile - variants, Schnitt - Varianten A, B, C



II
RG 2-6
01.01.2016
70

Rope, Hoop, Ball, Clubs, Ribbon

Use • Rhythmic Gymnastics


All hand apparatuses which are supposed to be used at FIG sanctioned events shall have markings according to FIG rules.

At FIG sanctioned events only FIG approved hand apparatuses shall be used.

Construction / Description of material, measurements


RG 2 Rope	Material: Hemp or similar suitable material Length: Optional for Senior and Junior Gymnasts Thickness: Uniform or reinforced in the centre. Shape: Both rope-ends, with or without knots. Without wooden-handle. May be wrapped with a thin non-slip material in a length corresponding to the width of a hand. Colour: Optional. Bright colour preferred
RG 3 Hoop	Material: Wood or synthetics Weight: 300 g. minimum Inner diam.: 800 – 900 mm Senior Gymnasts 700 – 900 mm Junior Gymnasts Can be wrapped Colour: Optional. Bright colour preferred.
RG 4 Ball	Material: Rubber or soft plastic, antistatic Weight: 400 g. minimum Diameter: 180 – 200 mm Senior and Junior Gymnasts Colour: Optional. Bright colour preferred.
RG 5 Clubs	Material: Wood or synthetics Length: 400 – 500 mm Senior and Junior Gymnast Weight: 150 g. min. Shape: Bottle shape Diameter of the head: 30 mm max. Colour: Optional. Bright colour preferred. Can be wrapped. (The head of the clubs must be fixed firmly to the neck of the apparatus. It shall not rotate)
RG 6 Gymnastic Ribbons	<i>Ribbon:</i> Material: Satin or similar Material: Total length 7 m in one piece. The end at which the ribbon is attached to the cane is folded and doubled in a length of 1 meter \pm 0.1 m. The ready-made ribbon has a total length of 6 meters, min. (5 meters, min for Juniors) Weight: 35 g. minimum, without the cane (30 g. min. for Juniors) Width: 40 – 60 mm Colour: Optional. Bright colour preferred.
RG 6 Gymnastic Ribbons Cane	<i>Cane :</i> Material: Wood, bamboo, fibreglass or synthetics Length: 500 – 600 mm Diameter: maximum 10 mm at the thickest point. Shape: cylindrical or conic. The handle may be wrapped in a thin anti-slip material with a length of 100 mm max. Colour: Optional. <i>Fixture :</i> Material: cord, nylon-thread or similar item, or moveable ring resp. a swivel attached to the cane. Length: 70 mm maximum

Rope, Hoop, Ball




Rope: Size of Logos		
"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm
"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	10 mm	± 2 mm
Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name		

Hoop: Size of Logos		
"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm
Position of the left side on the middle axes	at the inner side of the hoop	-
"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	10 mm	± 2 mm
Position of the left side on the middle axes	at the inner side of the hoop	-
Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name		



Ball: Size of Logos		
"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm
Distance from the valve	10 mm	± 5 mm
"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	10 mm	± 2 mm
Distance of the left side from the valve	10 mm	± 5 mm
Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name		

Clubs, Ribbon




routes longueurs en mm
all lengths in mm
alle Längen in mm

Clubs: Size of Logos

"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm
Distance to the body	20 mm	± 5 mm

"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	10 mm	± 2 mm
Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name		



routes longueurs en mm
lengths in mm
Längen in mm

Ribbons Cane: Size of Logos

"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm

"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	10 mm	± 2 mm
Distance to the 100 mm reinforcement	10 mm	± 2 mm
Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name		

Ribbon: Size of Logos

"Manufacturers Logo/Name"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm

"FIG Approved"		
(all values in mm)	value	Tolerance ±
width	10 mm	± 2 mm
length	30 mm	± 2 mm

Position at the beginning of the Ribbon and at the end of the Ribbon

Distance from the end	100 mm	± 20 mm
Distance from the beginning	50 mm	± 10 mm

Remark: The FIG Logo can be turned to arrange the same orientation as the Manufacturers Logo/Name

Measurement Table for RG with Balance

II
RG 10
01.01.2016
73

Use • Rhythmic Gymnastics for testing prescriptions of RG 3,4,5,6

Construction / Description of material, measurements

Form The apparatus consists of a table or a plate which can be placed on a table with special trays and tools for controlling prescribed parameters of RG equipment during the competition. An additional, suitable balance is needed.

Measurements The device should be suitable for measuring:

- Interior diameter of hoops (RG3) (Senior) : 800 – 900mm
- Interior diameter of hoops (RG3) (Junior) : 700 – 900mm
- diameter of balls (RG4) : 180 – 200mm
- diameter of the end of clubs (RG5) : 30mm max.
- diameter of the cane of gymnastic ribbons (RG6) : 10mm max.
- length of clubs (RG5) : 400 - 500mm
- length of ribbons (RG6) (Senior) : 6000mm min.
[can be measured as 6 * 1000mm]
- length of ribbons (RG6) (Junior) : 5000mm min.
[can be measured as 5 * 1000mm]
- length of the doubled part of ribbons (RG6) : 1000mm (+/- 100)
- length of the cane of gymnastic ribbons (RG6) : 500 - 600mm
- length of the optional handle part of the cane of gymnastic ribbons (RG6) : 100mm max.
- length of the fixture of gymnastic ribbons (RG6) : 70mm max.
- width of ribbons (RG6) : 40 - 60mm

The balance should be suitable for measuring the following weights ("masses") with a precision of +/- 1 g:

- hoops (RG3) : 300g min.
- balls (RG4) : 400g min.
- clubs (RG5) : 150g min.
- gymnastic ribbons without the cane (RG6, Seniors) : 35g min.
- gymnastic ribbons without the cane (RG6, Juniors) : 30g min.

The measurement trays for diameters of Hoops for measuring diameters shall control the whole circles, not only segments of the circles ("hoops shall not be bent during measurements"). Each Tray of 700mm, 800mm & 900 mm, must have a thickness minimum of 15mm.


All measures shall be indicated unmistakably on labels.

The weight of hoops shall be measured in a hanging position of the hoops.

Measurement Table for RG with Balance

II
RG 10
01.01.2016
74

Example for positioning of trays and tools for controlling the prescribed parameters:



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel



FLY TO THE GLORY

Chacott
www.chacott-jp.com



Official FIG Partner



Official RG Apparatus Supplier to Belarus

II
TRA
01.01.2014
75



2.4 TRA Trampoline Gymnastics

TRAMPOLINE-DIVERSITY. Since 1960.

EUROTRAMP®



EUROTRAMP.COM



II
TRA 1
01.01.2017
76

Trampoline

1. Frame

- 1.1. Interior measurements of the frame, with bed under tension, but without frame pads:

Length	505 cm +/- 6 cm
Width	291 cm +/- 5 cm
- 1.2. For safety reasons the profile of the frame must have rounded edges. The radius must be min 15mm. The profile of the frame may also be oval or round, but in these cases, it must be guaranteed, that coaches are able to stand on the frame safely in order to give the necessary support to the athletes. Special attention must be given to the padding of the frame.

2. Trampoline Bed

- 2.1. The height of the bed, measured from the floor, shall meet all of the following three specifications:
 - 2.1.1. At least one of the heights h_1 ; h_2 ; h_3 or h_4 (see figure) 115,5 cm +/- 0,5 cm
 - 2.1.2. All heights h_1 ; h_2 ; h_3 and h_4 (see figure) $\geq 115,0$ cm
 - 2.1.3. The heights h_1 ; h_2 ; h_3 and h_4 shall be adjusted, so that the bed is horizontal in all longitudinal and transversal directions with all four feet of the trampoline in firm contact to the ground.
- 2.2. Dimensions¹ of the bed under tension ready for use, including attachment straps:

Length (bl_1 ; bl_2 ; bl_3 ; see figure)	428 cm +/- 6 cm
	with: $\max(bl_1, bl_2; bl_3) - \min(bl_1, bl_2; bl_3) < 3$ cm
Width (bw_1 ; bw_2 ; bw_3 ; see figure)	214 cm +/- 5 cm
	with: $\max(bw_1, bw_2; bw_3) - \min(bw_1, bw_2; bw_3) < 3$ cm
- 2.3. The bed must be constructed from light coloured bands, webs, strings etc., which must be held together in such a way that they are not displaced during use.
 - 2.2.1. Web Construction:

Width of web under tension	0,55 cm +/- 0,15 cm
Distance between any two webs	1,6 cm (max.)
 - 2.2.2. String Construction:

Width of strings under tension	0,3 cm +/- 0,1 cm
Distance between any two strings no greater than	1 cm
- 2.4. The bed must be strong enough to withstand wear, and not tear when in use.
- 2.5. Two rectangular areas¹ must be marked out clearly in red lines. Each area must be symmetrically oriented to the middle of the bed. The width of the delimitation lines must be between 13 and 24 mm. The lines belong to the marked areas:

Area A (rectangle 215 * 108):

- the delimitation lines for area A shall not only define the rectangle area of 215 * 108 cm, but shall also be continued to the end of the bed (see figure).

¹ Trampoline beds are subject to considerable changes in dimensions due to the high tensions. All length specifications shall be fulfilled at the following instant of times:

Competition: At the time of the officially announced apparatus control before the competitions and thereafter.

During other official apparatus controls (i.e. test at a FIG test institute): After a period of 24h with the trampoline unfolded, ready for use and preconditioned with $20^\circ \pm 3^\circ$ C and a humidity of < 60%.

II
TRA 1
01.01.2017
77

Trampoline

Length (cl_1, cl_2, cl_3 , see figure)	215 +/- 4 cm
with: $\max(cl_1, cl_2, cl_3) - \min(cl_1, cl_2, cl_3) < 2$ cm	
Width (dw_1, dw_2, dw_3 , see figure)	108 +/- 4 cm
with: $\max(dw_1, dw_2, dw_3) - \min(dw_1, dw_2, dw_3) < 2$ cm	
Area B (quadratic 108 * 108):	
Length (el_1, el_2, el_3 , see figure)	108 +/- 4 cm
with: $\max(el_1, el_2, el_3) - \min(el_1, el_2, el_3) < 2$ cm	
Width (dw_1, dw_2, dw_3 , see figure)	108 +/- 4 cm
with: $\max(dw_1, dw_2, dw_3) - \min(dw_1, dw_2, dw_3) < 2$ cm	

The center of the bed must be indicated by a red cross.

Dimensions	70 cm +/- 3 cm
------------	----------------

3. Suspension

The bed must be suspended with springs in such a way as to present no danger to users. The tension on the bed should be such that the bed stabilises within a second after contact.

4. Area free of obstruction beneath the bed

The trampoline must be constructed so that the competitor will not touch any part of the frame beneath the bed.

5. Safety Padding

- 5.1. The frame and springs must be entirely covered by a shock absorbing padding, the thickness of which must be between 3,0 cm and 5,0 cm at the edge near the bed. At the edge over the frame the thickness must not be necessarily the same: It can increase up to 10 cm, however the maximum slope between the two edges shall not be higher than 10 degrees from horizontal plane. The padding must not touch any part of the bed. The padding may extend over the bed by up to 6 cm, but the available unobstructed jumping area may not be smaller than the minimum bed size (422 cm x 209 cm).
- 5.2. The padding should be firmly fixed to the frame without hindering the normal action of the bed and springs. It should not cause noise through flapping.
- 5.3. The bottom of the padding, at the side of the bed, should not protrude above the level of the bed by more than 6 cm. The padding must be stable enough to allow for a person to stand on it without protruding into the spaces between the springs.
- 5.4. The foam of the safety padding shall have a density of 30 kg / m^3 (+/- 3,0 kg / m³). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be $\geq 260 \text{ kPa}$, the compression stress value 40% shall be 70,0 (+/- 15,0) kPa (ISO 3386-1 – Amd1: 2010).

6. Safety Platform

- 6.1. Platforms must be placed at both ends of the trampoline. The platform must be made of a framework which is firmly attached to the trampoline. The platforms must be constructed so that it is shock absorbent and the surface must be covered with a shock absorbing mat, firmly fixed to the platforms.

The mats must have the following dimensions:

Width:	300 cm	+/- 2,5 cm
Length (including wedge, 40 cm)	240 cm	+/- 2,5 cm
Thickness at the bedside	7,5 cm	+/- 0,5 cm
Thickness at the end	20 cm	+/- 2,0 cm

The platforms dimensions must be such, that the mats are sufficiently supported to ensure, that on landing, it supports the weight of the competitor without collapsing or folding.


II
TRA 1
01.01.2017
78

Trampoline

The foam of the mats shall have a density of 25 kg / m^3 ($\pm 2,5 \text{ kg / m}^3$). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be $\geq 130 \text{ kPa}$, the compression stress value 40% shall be $4,0$ ($\pm 1,0$) kPa (ISO 3386-1 – Amd1: 2010).


- 6.2. The mat covering the platform shall end between inner and outer edge of the frame pad.
The distance to the inner edge of the frame pad shall be 5 to 8 cm. (see figure)
7. Safety mats on the ground: Mats shall rest on the ground around and between the trampolines for safety reasons. All mats shall be of the same height and type. One of the following two types shall be used:
 - a) Mats which satisfy the specifications of MAG11/WAG11/TRA11. (measures: Height: 20 cm, Width: 200cm, Tolerance: $\pm 1 \text{ cm}$).
 - b) Mats with a core which shall have a density of 25 kg / m^3 ($\pm 2,5 \text{ kg / m}^3$). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be $\geq 130 \text{ kPa}$, the compression stress value 40% shall be $4,0$ ($\pm 1,0$) kPa (ISO 3386-1 – Amd1: 2010). Ultimate tensile strength (ISO 1798: 2008) of the cover material shall be 560-600 kPa . (measures: Height: 20 cm min , Width: 200cm, Tolerance: $\pm 1 \text{ cm}$).

Trampoline



Trampoline

Specifications:
 Hauteur, longueur et largeur de la toile
 heigth, length and width measurements of the bed
 Höhe, Länge- und Breitenmessung



zones obligatoires; construction selon le gré; dessin en exemple	dimensions: mandatory; design: at your discretion; drawing: typical example	Masse bindend; Konstruktion freigestellt; Zeichnung als Beispiel
--	---	--

II
TRA 2
01.01.2014
81

Double Mini - Trampoline

1. Frame

- 1.1. For safety reasons no metal bars or other firm fixings are allowed across the ends of the Double Mini-Tramp other than at floor level.
- 1.2. For safety reasons the profile of the frame must have rounded edges. The radius must be minimum 15mm.
- 1.3. Safety Padding
 - 1.3.1. The frame and springs must be entirely covered by shock absorbing padding, the maximum Thickness of which must not be greater than 55mm. The padding must not cover any part of the bed.
 - 1.3.2. The padding should be firmly fixed to the frame without hindering the normal action of the bed and the springs. Nor should it cause noise through flapping.
 - 1.3.3. The bottom of the padding at the side of the bed should not protrude above the level of the bed by more than 6 cm.
 - 1.3.4. The bars beneath the bed must be padded.
 - 1.3.5. The frame ends on the dismount end must be covered with at least 50mm pads firmly joined together with the other padding.

2. Bed

- 2.1. The bed must be constructed from light coloured bands, webs, strings etc., which must be held together in such a way that they are not displaced during use.
- 2.2. Dimensions¹ of the bed under tension

Length $bl_1; bl_2; bl_3$ (see figure), edge to edge of included end markers	285 cm +/- 5 cm
with: $\max(bl_1, bl_2; bl_3) - \min(bl_1, bl_2; bl_3) < 10$ cm	
Width ($bw_1; bw_2; bw_3$; see figure), including attachment straps:	92 cm +/- 4 cm
with: $\max(bw_1, bw_2; bw_3) - \min(bw_1, bw_2; bw_3) < 2$ cm	
- 2.3. Height of bed, measured from the floor with bed under tension:

Mounting End	45 cm +/- 1,5 cm
Dismounting End	70 cm +/- 1,5 cm
- 2.4. Width of web under tension: 0,4 cm min. 1,3 cm max.
 Width of strings under tension: 0,3 cm +/- 0,1 cm
- 2.5. The strands of webbing (or string) must be sewn together, and the distance between any two strands must not be greater than 1, 8 cm (max: 1 cm with string-construction).
- 2.6. The bed must be strong enough to withstand wear, and not tear when in use.

¹ Double Mini Trampoline beds are subject to considerable changes in dimensions due to the high tensions. All length specifications shall be fulfilled at the following instant of times:

Competition: At the time of the officially announced apparatus control before the competitions and thereafter.

During other official apparatus controls (i.e. norm-control by TC members): After a period of 24h with the double mini trampoline unfolded, ready for use and preconditioned with $20^\circ \pm 3^\circ$ C and a humidity of < 60%.

II
TRA 2
01.01.2014
82

Double Mini - Trampoline

- 2.7. The Penalty Zones must be marked in red on the bed.

The dimensions of these zones are:

End markers	13 cm	+/- 2 cm
Centre zone	39 cm	+/- 1 cm
Distance of the Centre Zone (Measured from the mounting end)	90 cm	+/- 2 cm

3. Landing Area

- 3.1. The landing area shall be covered with a landing mat (TRA11) which is shock absorbent and which allows a stable landing on the feet.

Dimensions of the landing area must be:

Length (landing mat, TRA11)	600 cm	+/- 1 cm
Width (landing mat, TRA11)	300 cm	+/- 1 cm
Thickness (landing mat, TRA 11)	30 cm	+/- 1 cm

- 3.2. Additional safety mat behind the landing area

An additional safety mat with the minimum dimensions of 300 * 200 * 20 cm must be placed directly behind the landing area.

3.3. Landing Zones

Two landing zones must be marked out in the landing area, with either the whole zone in a contrasting colour or, with lines 50mm wide in a contrasting colour. If lines are used, they have to belong to their zones.

3.3.1. Landing Zone C:

The size of landing zone C is identical to the size of the Landing Area (see 3.1 above)

3.3.2. Landing Zone B:

The outer edge of the landing zone (or lines) marks the boundary of the landing zone, the dimensions of which must be:

Length	400 cm +/- 1 cm
Width	200 cm +/- 1 cm

3.3.3. Landing Zone A:

The outer edge of the landing zone (or lines) marks the boundary of the landing zone, the dimensions of which must be:

Length	250 cm +/- 1 cm
Width	100 cm +/- 1 cm

For certain events the FIG may stipulate the colours of the different zones.

4. Run-up

Floor mats shall be used on the run-up:


Length	2000 cm	+ 250 cm
Minimum Width	100 cm	
Thickness	2,5 cm	+/-0,5 cm

5. Safety mats on the ground: On the two sides of the DMT a mat shall rest on the ground for safety reasons (measures: Height: 20 cm, Width: 200cm, Tolerance: +/- 1 cm). They have to satisfy the specifications of MAG11/WAG11/TRA11.


6. No testing procedures for Double Mini-Trampolines at a test institute are available at the moment. The test must be performed by a federation who qualified with a team for the Men's Team Final in Double Mini-Trampoline at the last held World Championships. Further Procedures for Certification see Part III, 4.1. and 4.2.

II
TRA 2
01.01.2014
83


Double Mini - Trampoline




vue de face
front view
Frontansicht



vue de côté
side view
Seitenansicht



vue de dessus sur les deux surfaces, rectangulaires
top view, perpendicular to both areas
Aufsicht, rechtwinklig zu beiden Flächen



Variantes - détail profil du cadre
variants - detail profile of the frame
Varianten - Detail Rahmenprofil


cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

II
TRA 2
01.01.2014
85

Double Mini - Trampoline



II
TRA 3
01.01.2014
86

Tumbling track

1. Tumbling Track

- 1.1. The tumbling track must be constructed with a sprung surface, which must be padded. If constructed of several units these must be firmly fixed together as so not to separate in use and showing no space between them.

Dimension:

Length	2500 cm	+ 100 cm
Height	30 cm max (from 1.1.2012: ± 1 cm)	
Width of construction	200 cm	± 5 cm

1.2. Markings

Two lines, 50mm wide in a contrasting colour must mark the outer edge (boundary) of the track.

Distance (incl. lines): 150 cm ± 1 cm

A centre line, 5 cm wide, in a contrasting colour, must mark the centre line of the tumbling track.

2. Landing Area

- 2.1. The landing area shall be covered with a landing mat (TRA11) which is shock absorbent and which allows a stable landing on the feet. The height of the landing mat shall be equal to the height of the tumbling track.

Dimensions of the landing area must be:

Length (landing mat TRA11)	600 cm	± 1 cm
Width (landing mat TRA11)	300 cm	± 1 cm
Thickness (landing mat TRA11)	30 cm	± 1 cm

2.2. Additional safety mat behind the landing area

An additional safety mat with the minimum dimensions of 300 * 200 * 20 cm must be placed directly behind the landing area.

2.3. Landing Zone

A landing Zone must be marked out in the landing area, with either the whole zone in a contrasting colour or, with lines 50mm wide in a contrasting colour. The outer edge of the landing zone (or lines) marks the boundary of the landing zone, the dimensions of which must be:

Length	400 cm ± 1 cm
Width	200 cm ± 1 cm

A non-compulsory supplementary mat in the same dimension as the landing zone can be used (TRA13). In this case the supplementary mat must be attachable to the landing mat (i.e. using Velcro). The colour of the supplementary mat must be in contrast to the landing mat and the tumbling track or with lines according to the description above.

3. There must be a run up area (same level as tumbling track) prior to the tumbling track.


Dimensions:

Length	1000 cm	+100 cm
Minimal width	100 cm	

4. There must be a hard and a soft Vaulting Board available which meets the specifications of TRA 14.

II
TRA 3
01.01.2014
87

Tumbling track



Landing mat
Double Mini-Trampoline + Tumbling
Safety mat
Trampoline, Double Mini-Trampoline

II
TRA 11
01.01.2006
88

Use • Double Mini-Trampoline; Tumbling; Trampoline

Construction / Description of material, measurements

Form	The surface must be horizontal, even and without gaps. To arrange the whole area several mats can be composed.
Measurements	Height safety mat Trampoline; DMT (TRA1, TRA2): 20 cm +/- 1 cm Height landing mat DMT; Tumbling (TRA2, TRA3): 30 cm +/- 1 cm
Functional Properties	<p>Absorbency: The mats must absorb motion energy, in order to reduce the reaction transmitted to the body of the landing gymnast, to a tolerable proportion.</p> <p>They must respond to increased penetration with an evenly increasing resistance.</p> <p>Stability and Freedom of Movement : Absorbency of the mats must be balanced in order to guarantee standing, walking stability and freedom of movement; there must be an equal balance between elasticity and absorbency properties.</p> <p>Indentations caused by the incidence of compressive forces must not encase the body parts, thereby hindering freedom of movements mainly of rolling a part of the body.</p> <p>If a cover is used, such cover may not cause any hindering folds. The mats' upper surface material must offer a balance between anti-slip and slippage. It must be neither slippery nor possess inhibitory resistance.</p> <p>By no means should mats be dislocated during performances. An anti-ski cover on the mats' underside may provide this condition.</p> <p>The border zones of the mats which are pushed together should practically have the same functional properties as the remaining surface. Impacts on the border zones should not cause different indentations than on the remaining surface. For this purpose, and to bridge joints, continuous runners are permitted.</p>
Colour	<p>Preference should be given to uniform colours.</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour for certain events.</p>
<p align="center">Norms / Functional properties Regarding tests carried out by FIG Tests Institutes : please see chapter IV</p>	

Landing mat
Double Mini-Trampoline + Tumbling
Safety mat
Trampoline, Double Mini-Trampoline

II
TRA 11
01.01.2006
89

Use	•	Double Mini-Trampoline; Tumbling; Trampoline
-----	---	--

Use	•	Trampoline; Double Mini-Trampoline;
-----	---	-------------------------------------

Construction / Description of material, measurements

Form	Spotter mats must be covered with a material which will slide easily. The mats must be provided with at least two handles or one long handle on the two long sides of the mat.		
Measurements	Length	200 cm	- 50 cm
	Width	150 cm	- 50 cm
	Thickness	15 cm	- 5 cm
Functional Properties	The foam of the spotter mats shall have a density of 20 kg / m ³ (+/-2 kg /m ³). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be ≥ 90 kPa, the compression stress value 40% shall be 2,5 (+/- 0.5) kPa (ISO 3386-1: 1986 – Amd1: 2010).		
Colour	<p>Preference should be given to uniform colours.</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour for certain events.</p>		

Supplementary mat Tumbling

II
TRA 13
01.01.2016
90

Use • Tumbling;

Construction / Description of material, measurements

Use	A supplementary mat must be available for the landing area in Tumbling. The usage is not compulsory.
Form	Their upper surface must be horizontal, even and without gaps. It shall have the size of the landing zone. The supplementary mat can be laid on the landing mats (TRA11), if used it must be attachable to the landing mat (i.e. using Velcro).
Measurements	<p>Height of the supplementary mat: 10 cm * 1 cm</p> <p>Surface: 400 x 200 cm * 1 cm</p> <p>* Tolerance +/-</p>
Functional Properties	<p>The foam of the supplementary mats shall have a density of 25 kg / m³ (+/- 2,5 kg / m³). The ultimate tensile strength of the foam (ISO 1798: 2008) shall be ≥ 115 kPa, the compression stress value 40% shall be 4,0 (+/- 1.0) kPa (ISO 3386-1: 1986 – Amd1: 2010).</p> <p>Their upper surface must be horizontal, even and without gaps. The supplementary mats have to be laid on the landing mats. The supplementary mat shall be attachable (i.e. using Velcro).</p>
Colour	<p>The colour of the supplementary mat must be in contrast to the landing mat and the tumbling track or with lines according to the description of the landing zone (see TRA3).</p> <p>The upper surface must not show optically disturbing patterns or insignia.</p> <p>The FIG may designate the colour for certain events.</p>

Vaulting Board

II
TRA14
01.01.2016
91

Use • Tumbling “hard” and “soft”

Construction / Description of material, measurements

Form

The profile of the vaulting board must adhere exactly to the respective blue print.

Its upper surface rises in an arched form, approaching the horizontal between 75 cm and 95 cm, measured from the frontal angle. The height reached at this point, may not be exceeded. After this point, the upper surface may continue horizontally or slope downward.

The rise of the arch is 3.5 cm +/- 0,5 cm.

For competitions a “soft” and a “hard” vaulting board shall be available. The “hard” board shall be marked with a dot on the surface.

Measurements

- Length	120 cm	* 1 cm
- Width	60 cm	* 1 cm
- Height	20 cm	* 1 cm
- Height (run-up side)	max 3 cm	
- Cushion Cover	2 cm	* 0,5 cm
- Total height with cushion cover	22 cm	* 1,5 cm
- Free space between floor and the lower edge of the vaulting board at the run-up side	max. 1 cm	

*Tolerance +/-

The stipulated length and height refers to the vertical projection of the upper plate, i.e. the take-off plate.

The base may be larger, but cannot extend more than 2 cm beyond the projection of the board.

Labelling of the “hard” vaulting board on the surface by a dot with clear contrast on the longitudinal midline:

Distance to the side of run up	5 cm
Diameter	8 cm

Functional Properties

The functional properties of the vaulting board (hardness, damping, elasticity) shall not be adjustable (i.e. springs must be fixed so that they cannot be easily removed by hand).

The elasticity of the vaulting board must be most effective in the area between 75 cm and 95 cm, measured horizontally from the frontal angle.

The vaulting-board must dampen the counter pressure, i.e. reduce motion energy.

Elasticity and absorbency must be evenly distributed, so that the effect of the vaulting board differs only slightly, regardless whether the force of the impact is at the middle axis, or away from it.

Vaulting Board

II
TRA14
01.01.2016
92

Colour

The upper surface of the vaulting board must offer slip resistance.

The board must not produce disturbing sounds during its use.

The board shall not slide at the time of impact of the athlete. This shall be achieved by anti-slip devices at the bottom side of the board. The slip resistance shall be provided especially when the board bottoms out at the middle part.


The vaulting board and its base may not have any sharp corners, edges and no protruding parts. Mainly the upper and under edge of the upper part of the Vaulting board towards the apparatus side (Vaulting Table, Balance Beam of Uneven Parallel Bars) shall be cushioned and rounded.

The choice of colour is left to the discretion of the manufacturer.

With exception of the dot for "hard" vaulting boards optically disturbing patterns, stripes or insignia on the upper surface are not permitted.

The FIG may designate the colour for certain events.

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV



cotes obligatoires;
construction selon le gré;
dessin en exemple

dimensions: mandatory;
design: at your discretion;
drawing: typical example

Maße bindend;
Konstruktion freigestellt;
Zeichnung als Beispiel

Time measurement device for trampoline competitions - TMD

II
TRA 15
01.01.2014
94

- | | |
|-----|---|
| Use | <ul style="list-style-type: none"> Helping device for judging individual and synchronized competitions |
|-----|---|

Construction / Description of material

General Requirements

The device must be able to measure deductions due to asynchronous landing in synchronized competitions as well as a sum of the flight times for the skills in individual competitions.

General Functions

- Mode for synchronized competitions:
The device is attached to the two trampolines which are used for the competition. It has to be administrated by a specialized judge who is responsible for the evaluation of the score of synchronization (S). After a "Start" during the flight phase of the first element the device shall register all time intervals between the landings of the gymnasts. After the end of the routine the device has to calculate, to indicate and to memorize the deductions for each skill and the total score for synchronization according to a conversion ratio between time intervals and deductions (TRA Code of Points).

- Mode for individual competitions:
The device is attached to the trampoline which is used for the competition. It has to be administrated by a specialized judge. After a "Start" during the flight phase of the first element the device shall register all time intervals between take-offs and the landings of the gymnast (flight times) including the flight time of the first element. At the end of the routine the device has to calculate, to indicate and to memorize the flight times of the elements as well as their sum (up to 10 skills).

Definitions

Measurement Lines: At least three parallel lines along the longitudinal side of the trampoline's bed. The lines are arranged ≤ 100 mm below the under surface of the unloaded bed built-in a trampoline which is ready for use. One line shall be exactly below the middle of the jumping zone and at least two others are running in a distance of 540 (± 5)mm from the middle line of the bed directly below the lateral boundaries of the jumping zone (see drawing).

Starting Point at Foot Contact: The point in time of the first contact of the gymnast with at least one of the Measurement Lines by impacting on the trampoline's bed. At that time a measurable signal for the TMD shall be provoked.

Ending Point at Foot Contact: The point in time of the release of the gymnast from all Measurement Lines by taking off from the trampoline's bed. At that time a measurable signal for the TMD shall be provoked.

Time Difference in Landing: Time interval at the landing after the same synchronous jump between the Starting Point at Foot Contact of the first athlete and the Starting Point at Foot Contact of the partner, expressed in seconds rounded down to the next lower multiple of 0,005 s (e.g.: All values less than 0.005 s are rounded to 0.000 s, all values equal or higher than 0.005 s and less than 0.01 s are rounded to 0.005 s).

Time of Flight: Time interval during the flight phase of a jump between an Ending Point at Foot Contact and a succeeding Starting Point at Foot Contact, expressed in seconds rounded down to the next lower multiple of 0,005 s. (e.g.: All values less than 0.005 s are rounded to 0.000 s, all values equal or higher than 0.005 s and less than 0.01 s are rounded to 0.005 s).

Total Time of Flight: Sum of all measured Time of Flights during an exercise of an individual competition beginning with the first skill, expressed in seconds. This value in seconds is equivalent to the score for the total time of flight in points.

Start: The point in time fixed by a switch-key to be pressed by a specialized judge during the flight phase of the first element; from this time on the TMD records signals at landings of the athlete on the trampolines bed. For individual competitions the device has to remember the preceding Ending Point at Foot Contact to register the Time of Flight of the first element.

Stop: The point in time fixed by a switch-key to be pressed by a specialized judge, from this time on the TMD records no more signals at landings of the athlete on the trampoline's bed.

Deduction for unsynchronized Landing: Deduction in points for the synchronization of each element according to a conversion from the Time Difference in Landing according to the TRA Code of Points.

Example 1: Calculation for the Deduction for an unsynchronized Landing with a factor of 2.5, rounded to 1/10 and a special treatment for less than 0.01 s (*) and more than 0.20 s () (TRA Code if points 2009):**

Time difference in landing (s)	Deduction (pts)
$0,00 \leq x < 0,01$	0,0 pts (*)
$0,01 \leq x < 0,06$	0,1 pts
$0,06 \leq x < 0,10$	0,2 pts
$0,10 \leq x < 0,14$	0,3 pts
$0,14 \leq x < 0,18$	0,4 pts
$0,18 \leq x \leq 0,20$	0,5 pts
if $x > 0,2$ then $x := 0,2$ s and deduction := 0,5 pts (**)	

(*) special treatment for less than 0,01 s.

(**) special treatment for more than 0,20 s.

Sum of Deduction: Accumulation of the Time Differences in Landing after each landing multiplied by 2,5 to give a total deduction rounded to 0,1 pts for all skills. As long as the unrounded sum is below 0,05 the corresponding sum of deduction shall be 0,0 pts. (***) (see example 2)

Synchronization Score: The Synchronization Score should be shown as maximum 10,0 pts minus the Sum of deductions in case of 10 skills (see example 2). Otherwise the maximum score equals the number of the counted skills (for example 5,0 pts for 5 skills).

Example 2: Calculation for the Sum of deduction and the Synchronization Score for a full exercise with 10 skills.

Time differences in landing (s)	Acc.[rounded down] (s)	Sum of Deduction (pts)
$0,00 \leq x < 0,05 \rightarrow 0,0$ pts (***)		
1st skill $x := 0,015$	0,015	0,0375 \rightarrow 0,0 pts (***)
2nd skill $x := 0,035$	0,050	0,125 \rightarrow 0,1 pts
3rd skill $x := 0,120$	0,170	0,425 \rightarrow 0,4 pts
4th skill $x := 0,295$	0,370 (**)	0,925 \rightarrow 0,9 pts
5th skill $x := 0,430$	0,570 (**)	1,425 \rightarrow 1,4 pts
6th skill $x := 0,030$	0,600	1,500 \rightarrow 1,5 pts
7th skill $x := 0,005$	0,600 (*)	1,500 \rightarrow 1,5 pts
8th skill $x := 0,115$	0,715	1,7875 \rightarrow 1,8 pts
9th skill $x := 0,005$	0,715 (*)	1,7875 \rightarrow 1,8 pts
10th skill $x := 0,010$	0,725	1,8125 \rightarrow 1,8 pts
Sum of deduction :=		1,8 pts
Synchronization Score :=		8,2 pts

Time measurement device for trampoline competitions - TMD

II
TRA 15
01.01.2014
96

Specific Requirements	<p>(*) special treatment for less than 0,01 s. (**) special treatment for more than 0,20 s. (***) Deduction := 0,0 pts as long as the unrounded sum is below 0,05</p>
Technical Features	<p>The device shall not interfere with the performance of the athletes nor shall it provoke any restriction of the functional properties of the trampoline. The detectors for the Starting and Ending Points at Foot Contact shall be installable at any standardized trampoline. The fixation shall be below the apparatus (trampoline with padding and safety platform) with no protruding parts. If there are cable connections, they must be long enough to reach the displacement specifications given for the "Arena for Trampoline Competitions" (see: Part II 4. Competition area; TRA). All other components of the device shall be out of the area of the safety mats on the ground.</p> <p>If emitters with optical beams are used, they shall not harm eyes of participants, judges, spectators or other staff.</p> <p>If emitters of radio waves are used, they shall not have a capacity of more than 0,01 watts in a frequency range of 27 megahertz and above.</p> <p>If the device needs external power, it must be provided with backup power, providing a battery life for at least 5 minutes after disconnecting the external power source.</p> <p>The system must provide time measurements with an error lower than $\pm 0,005$ s.</p> <p>The TMD shall come with an English written documentation containing a user's guide and all necessary technical descriptions.</p> <p>The control device shall contain a set of buttons, indicators and components with the following features:</p> <ul style="list-style-type: none"> • SELECT MODE – individual or synchronized competition • RESET – Preparation for a new measurement • START– start the measurement of an exercise, indicated by a sound • STOP – stop the measurement of an exercise • VIEW – MODE – with the following possibilities: Synchronized competition mode: Selection for each skill (from 1 to 10) with the calculated Deductions for unsynchronized Landing as well as the Synchronization Score for the whole exercise. Individual competition mode: Selection for each skill (from 1 to 10) with the registered Times of Flight as well as the Total Time of Flight for the whole exercise. • Possibilities for a manual change of the Preliminary Synchronization Score with an increment of 0,2 points. • Components to ensure proper function of the sensors. • Components to indicate proper function of the power supply. • Connection devices and software to transfer all data to a personal computer using a standard method of data transmission (USB, Firewire etc.). • Software to memorize and print all data on a personal computer with the following details: <ul style="list-style-type: none"> - Time Differences in Landing and corresponding Deductions for unsynchronized Landing for all skills (from 1 to 10) as well as the Synchronization Score for the whole exercise for synchronized competitions. - Times of Flight for all skills (from 1 to 10) as well as the Total Time of Flight for the whole exercise for individual competitions.

Time measurement device for trampoline competitions - TMD

II
TRA 15
01.01.2014
97

Procedures for Approval

The approval of a TMD shall include the following steps:

- Confirmation by a member federation of the FIG (operation at a competition without technical problems; see: FIG Apparatus Norms Part III, clause 4.1).
- Presentation at a testing institute (forwarding a full technical documentation written in English and the complete equipment, if necessary with a special adapter according to: FIG Apparatus Norms Part IV TRA15 - TMD)
- Documented report by a TC member ordered by the FIG-TC-TRA-President about the functional status during a FIG competition

With successful fulfilment of all procedures the certification shall be given by the General Secretary.

II
ACRO
01.01.2006
98



2.5 ACRO Acrobatic Gymnastics

II
ACRO 1
01.01.2009
99

Floor

Use • Acrobatic Gymnastics


Construction / Description of material, measurements

Form	<p>The Performance Area shall have a square format. The surface must be horizontal, even and without gaps</p> <p>Border :</p> <p>Horizontal and even, at the same height of the performance area</p> <p>Border's variant :</p> <p>Width 50 cm, horizontal and even, at the same height of the performance area. The next 50 cm are inclined; the slope may not exceed 25%, max.</p> <p>Safety zone:</p> <p>The safety zone shall be kept totally free as a surrounding zone around the performance area and the border. It shall be horizontal, even and without gaps.</p>																					
Measurements	<table><tr><td>Performance area</td><td>1200 cm x 1200 cm</td></tr><tr><td></td><td>Tolerance +/- 3 cm</td></tr><tr><td>Diagonals of the performance area:</td><td>1697 cm +/- 5cm</td></tr><tr><td>Border</td><td>100 cm, min.</td></tr><tr><td>Border as a variant:</td><td></td></tr><tr><td>Horizontal area, Width</td><td>50 cm, min.</td></tr><tr><td>Slope max. 25 %, Width</td><td>50 cm, min.</td></tr><tr><td>Height of outer border at the very end</td><td>3,5 cm, max.</td></tr></table> <p>When there is an delimitation strip between the performance area and the border :</p> <table><tr><td>Width of delimitation strip</td><td>5 cm,</td></tr><tr><td></td><td>Tolerance +/- 0,5 cm</td></tr></table>		Performance area	1200 cm x 1200 cm		Tolerance +/- 3 cm	Diagonals of the performance area:	1697 cm +/- 5cm	Border	100 cm, min.	Border as a variant:		Horizontal area, Width	50 cm, min.	Slope max. 25 %, Width	50 cm, min.	Height of outer border at the very end	3,5 cm, max.	Width of delimitation strip	5 cm,		Tolerance +/- 0,5 cm
Performance area	1200 cm x 1200 cm																					
	Tolerance +/- 3 cm																					
Diagonals of the performance area:	1697 cm +/- 5cm																					
Border	100 cm, min.																					
Border as a variant:																						
Horizontal area, Width	50 cm, min.																					
Slope max. 25 %, Width	50 cm, min.																					
Height of outer border at the very end	3,5 cm, max.																					
Width of delimitation strip	5 cm,																					
	Tolerance +/- 0,5 cm																					
Functional Properties	<p>Performance area and border :</p> <ul style="list-style-type: none">- Equal elasticity on the surface as well as dampening.- When in use it should not have any disturbing motion energy.- Elasticity and dampening must be balanced in such a way that they guarantee the gymnast stability and freedom of movement. It must not restrict turns and slide movements.- The surface cover of the Performance area must provide a balance between anti-skid and slippage. It must not cause skin burns.- The floor must not produce disturbing sound during the execution of an exercise. It must assure a low noise level.																					
Colour	<p>Of plain colour which choice is left to the manufacturer's discretion. Dark colours are not allowed. For certain events the FIG may stipulate the colours. The delimitation shall have a clear contrast to the performance area.</p>																					
Delimitation Strip	<p>The delimitation strip is part of the performance area.</p>																					

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes: please see chapter IV


II
ACRO 1
01.01.2009
100

Floor



- surface de compétition, arena, Wettkampffläche
- cadre, edge, Umrandung
- zone de sécurité, safety zone, Sicherheitszone

variantes, profile - variants, Schnitt - Varianten A, B, C



II
ACRO 11
01.01.2009
101

Landing Mat

Use • Acrobatic Gymnastics

Construction / Description of material, measurements

Use	For landing a mat shall be available. The use is not compulsory.
Form and functional properties	The functional properties of the landing mat must be identical to those of the landing mats MAG 11 and WAG 11.
Measurements	The minimum size of the landing mat is 200 cm x 150 cm x 20 cm

II
AER
01.01.2009
102



2.6 AER Aerobic Gymnastics

Performance area

II
AER 1
01.01.2014
103

Use • Aerobic Gymnastics

Construction / Description of material, measurements

Form	<p>The Performance Area shall have a square format. The surface must be horizontal, even and without gaps. Under load there shall not occur steps at the border of the plates.</p> <p>Border : Horizontal and even, at the same height as the performance area</p> <p>Safety zone: The safety zone shall be kept totally free as a surrounding zone around the performance area and the border. It shall be horizontal, even and without gaps.</p> <p>Delimitation strip: The competition area shall be surrounded by a black delimitation strip. The delimitation strip is part of the performance area.</p>															
Measurements	<table><tr><td>Performance area (Single)</td><td>700 cm x 700 cm Tolerance +/- 3 cm</td></tr><tr><td>Diagonals of the performance area:</td><td>990 cm +/- 5cm</td></tr><tr><td>Performance area (Duo, Trio, Groups):</td><td>1000 cm x 1000 cm Tolerance +/- 3 cm</td></tr><tr><td>Diagonals of the performance area:</td><td>1414 cm +/- 5cm</td></tr><tr><td>Width of the black delimitation strip</td><td>5 cm, Tolerance +/- 0,5 cm</td></tr><tr><td>Border</td><td>100 cm</td></tr><tr><td>Safety border</td><td>100 cm</td></tr></table>	Performance area (Single)	700 cm x 700 cm Tolerance +/- 3 cm	Diagonals of the performance area:	990 cm +/- 5cm	Performance area (Duo, Trio, Groups):	1000 cm x 1000 cm Tolerance +/- 3 cm	Diagonals of the performance area:	1414 cm +/- 5cm	Width of the black delimitation strip	5 cm, Tolerance +/- 0,5 cm	Border	100 cm	Safety border	100 cm	
Performance area (Single)	700 cm x 700 cm Tolerance +/- 3 cm															
Diagonals of the performance area:	990 cm +/- 5cm															
Performance area (Duo, Trio, Groups):	1000 cm x 1000 cm Tolerance +/- 3 cm															
Diagonals of the performance area:	1414 cm +/- 5cm															
Width of the black delimitation strip	5 cm, Tolerance +/- 0,5 cm															
Border	100 cm															
Safety border	100 cm															
Material	Parquet flooring – laminate or synthetics.															


Performance area

II
AER 1
01.01.2014
104


Functional Properties	<p>Performance area and border :</p> <ul style="list-style-type: none"> - Equal elasticity and dampening. - When in use no unrequested counter movements shall occur. - Elasticity and dampening must be balanced in such a way that they guarantee the gymnast stability and freedom of movement. It must not restrict turns and slide movements. - The surface cover of the Performance area must provide a balance between anti-skid and slippage. It must not cause skin burns. - The floor must not produce disturbing sound during the execution of an exercise. It must assure a low noise level.
Colour and Gloss	<p>Of plain colour, not shiny. The choice is left to the manufacturer's discretion. Dark colours are not allowed.</p> <p>Gloss – measurements according to International Standards (ISO 2813; ASTM D 523; DIN 67530) with a standardized reflectometer at an angle of illumination of 85° shall show gloss values of $R'_{85} \leq 30$ GU and may also not be shiny under competition conditions. (For detailed description of the reflectometer procedure see: Part IV AER1)</p> <p>The competition area shall be surrounded by a black delimitation strip.</p>

Norms / Functional properties
Regarding tests carried out by FIG Tests Institutes : please see chapter IV

II
AER 1
01.01.2014
105



variantes, profile - variants, Schnitt - Varianten A, B, C



II
01.01.2015
106


Use • Aerobic Gymnastics

Construction / Description of material, measurements

Form	The surface of the Step must be horizontal and not slippery. It can be covered by an anti-slip layer. To avoid injuries the Step shall not exhibit any sharp corners or edges that could be reached during regular use in a competition.
Measurements	<p>Height of the Step 150 mm +/- 10 mm</p> <p>Length of the horizontal upper part of the surface: 885 mm +/- 15 mm</p> <p>Width of the horizontal upper part of the surface: 275 mm +/- 10 mm</p> <p>Length of the Step at the base: 970 mm +/- 10 mm</p> <p>Width of the Step at the base: 370 mm +/- 10 mm</p> <p>Mass of the Step: $\geq 5,0$ kg</p>
Material	<p>Body of the Step: Plastics or other synthetic material</p> <p>Anti-slip covering: Plastics or other synthetic material</p> <p>The body and the anti-slip covering do not have to be of the same material.</p>
Functional Properties	<ul style="list-style-type: none"> - The surface of the Step must provide a sufficient slip resistance when it is used under competition conditions (with sneakers). - The contact area between Step and floor must provide a sufficient slip resistance. - The Step must not produce disturbing sound during the execution of an exercise. It must assure a low noise level. - The support must not be separable from the body of step. - The contact area between the Step and the floor must be such, that the Aerobic Floor is not damaged with scratches

Norms / Functional properties

II
01.01.2015
107



II
01.01.2009
108

3. Surfaces of apparatus, safety zones,
total surfaces

II
01.01.2009
109

Discipline	Apparatus	Area (meters)	Height of hall (prescription) if so from Podium (min. meters)	Height of hall International Arena (recommended) if so from Podium (min. Meters)
MAG Men's Artistic Gymnastics	MAG 1 Floor	18.00 x 18.00	7.00	8.00 – 10.00
	MAG 2 Pommel Horse	4.00 x 4.00		
	MAG 3 Rings	6.00 x 6.00		
	MAG 4 Vaulting Table	5.00 x 35.00		
	MAG 5 Parallel Bars	6.00 x 12.00		
	MAG 6 Horizontal bar	6.00 x 12.00		
WAG Women's Artistic Gymnastics	WAG 1 Vaulting Table	5.00 x 35.00	6.00	8.00 – 10.00
	WAG 2 Uneven Bars	6.00 x 14.00		
	WAG 3 Balance Beam	6.00 x 18.00		
	WAG 4 Floor	18.00 x 18.00		
RG Rhythmic Gymnastics	RG 1 Performance area	18.00 x 18.00	8.00	10.00 – 12.00
AER Aerobic Gymnastics	AER 1 Performance area	18.00 x 18.00	6.00	8.00 – 10.00
TRA Trampoline Gymnastics	TRA 1 Trampoline (synch.)	15.00 x 15.00	8.00	10.00 – 12.00
	TRA 2 Double Mini Trampoline	5.00 x 35.00	6.00	8.00 – 10.00
	TRA 3 Tumbling Track	5.00 x 45.00	5.00	
ACRO Acrobatic Gymnastics	ACRO 1 Performance area	18.00 x 18.00	7.00	8.00 – 10.00


II
01.01.2009
110

4. Competition area

Recommended Standards. For FIG Events the Placement of the Apparatuses and Podiums has to be approved by the FIG.


Arena – men's artistic gymnastics

II
MAG
01.04.2015
111



Arena – women's artistic gymnastics

II
WAG
01.4.2015
112




Requirements for Podiums and Anchors at MAG and WAG Competitions

II
MAG/WAG
01.01.2014
113

Construction / Measurements

Measurements	<p>Size of the podiums: See recommended standards on the proceeding pages.</p> <p>Height: 80 to 100 cm</p>
Requirements	<p>The podiums must be stable enough to withstand the forces which are transmitted by the gymnastics apparatuses.</p> <p>During competition no disturbing vibrations and movements shall occur in the podium.</p> <p>Special devices (i.e. additional, heavy supporting plates with sufficient area) should be used if the ground below the podiums is not hard enough.</p> <p>Additional columns shall be placed directly below the podium zones with high loads (i.e. below the stands of all gymnastics apparatuses).</p> <p>Floor anchors and equipment attachments)* on the ground shall be controlled by the local organizer of the competition before establishing the gymnastic equipment and podium. All attachments shall withstand a static force of 8000 N (+20N) in the pulling direction)**. This requirement must be fulfilled for both competition site and training sites.</p> <p>The stairs to the podium shall not have rails.</p> <p>)* Equipment attachments are all devices which do not belong to the homologated standard parts of the apparatus (i.e. Horizontal bar, ring frame etc.)</p> <p>)** "pulling direction" means: The direction of the cable at a correctly mounted equipment. After the application of a static force as described for 1 min (+10s) in pulling direction, no permanent deformation shall be observed at the anchors and/or the equipment attachments.</p>



Dream of Gymnastics

SASAKI®

- Official Partner of F.I.G.
- Certified Supplier of Apparel and Apparatus for Japan Gymnastic Association
- Official Supplier for Bulgarian R.G. Federation

II
TRA
01.01.2011
116

5. Apparatus Control Forms

Apparatus Control Forms – MAG, WAG, TRA and RG Forms A and Forms B

II
01.01.2014
117

Prior to every FIG Event in MAG, WAG, TRA and RG an apparatus control shall be scheduled before the first contact of athletes with the equipment. The completed forms have to be reported to the TC President or if he is not at the competitions site to the FIG Event Delegate and to the President of the FIG Apparatus Commission. According to the FIG event, different forms shall be used:

Form A: (FIG TC Delegate)

Competitions: World Cups, Continental Games (without FIG Apparatus manager)

Main aspects for the apparatus control with form A:

- To be performed 1-2 h prior to the first contact of the athletes with the equipment.
- To be done for training hall (every set), warming up hall and competition hall.
- Control of specifications of the FIG Apparatus Manual.
- Judgment of non-described safety relevant aspects.
- Control of all adjustable heights, lengths etc. at the apparatuses.
- Control of all security relevant parts (fixings, stability and mats displacement).
- If necessary monitoring of apparatus relevant ad hoc decisions of the TP / TC or other FIG Authorities.

Form(s) B: (FIG Apparatus Manager)

Competitions: World Championships and Olympic Games (with FIG Apparatus Manager)

Main aspects for the apparatus control with forms B:

(IC) Intensive Control (FIG Apparatus manager):

- To be done for training hall (every set), warming up hall and competition hall
- To be performed 1-2 h prior to the first contact of the athletes with the equipment
- Control of accordance of equipment with the tested Specimen
- Control of all specifications of the FIG Apparatus Manual
- Judgment of non-described safety relevant aspects
- Report of the results to the Technical President
- If necessary monitoring of apparatus relevant ad hoc decisions of the TP / TC or other FIG Authorities

(FC) Final Control (Technical Committee Member(s), FIG Apparatus Manager and President of the FIG Apparatus Commission):

- To be performed 1/2h prior to the competition or the podium training.
- Control of all adjustable heights, lengths etc. at the apparatuses.
- Control of all security relevant parts (fixings, stability and mats displacement).

(LC) Daily Light Control (FIG Apparatus Manager):



- To be performed every day in all training and warming up halls.
- Control of accordance of the equipment with the time of the extensive control.
- Control of all adjustable heights, lengths etc. at the apparatuses.
- Control of all security relevant parts (fixings, stability and mats displacement).

Remark: Forms B are published in FIG Apparatus Norms Part IV.

MAG - Apparatus Control Form A

(Forms B: see FIG Apparatus Norms Part IV)

II
MAG
01.01.2014
118

 APPARATUS CONTROL A - MAG GYMNASTICS 		
Apparatus: MAG	Competition: Name of the Competition	Date:
Note: Measurements taken from the floor to the top of the apparatus		
Floor	Stipulation	Result - Action
Surface area	12x12m including delimitation line	
Elasticity of floor		
Chalk box for feet		
Pommel Horse	Stipulation	Result - Action
Height of horse	115 cm +/- 1 cm, measured from floor	
Levers and knob covered	Protection of anchor and floor support	
Height of landing mats	10 cm +/- 1 cm	
Dimension of mat surface	min. 400 cm x 400 cm	
Still Rings	Stipulation	Result - Action
Height of rings	280 cm +/- 1 cm, measured from floor	
Dimension of mat surface	min. 200 cm x 500 cm	
Core and surface of mat	visual and tactile control of the landing area under the rings. Damages?	
Vaulting Table	Stipulation	Result - Action
Height	135 cm +/- 1 cm measured 68cm from landing end	
Levers and knob covered		
Protection of anchor and floor supports under apparatus		
Protection for space between landing mat and vaulting table		
Safety collar: different color from carpet of spring board		
Enhanced color of round-off hand placement mat		
Parallel Bars	Stipulation	Result - Action
Height of bars	200 cm +/- 1 cm from floor	
Distance between bars	42 cm to 52 cm	
Mat between bases	Total mat surface horizontal, even, without gaps	
Dimension of mat surface	min. 450 cm x 1100 cm	
Horizontal Bar	Stipulation	Result - Action
Height of bars	280 cm +/- 1 cm, measured from floor	
Dimension of mat surface	min. 300 cm x 1200 cm	
2 extra soft landing mats	200 cm * 400 cm	
Springboards	Stipulation	Result - Action
Height	20 cm +/- 1 cm, Cushion cover 2 cm +/- 0,05 = Total 22 cm +/- 1,5 cm	
1 hard and 1 soft board at the vault	hard board marked with a dot springs fixed	
1 soft board at the parallel bars	springs fixed	
Mats	Stipulation	Result - Action
Height of all landing mats	20 cm +/- 1 cm (except pommel horse -10 cm)	
Height of all extra soft landing mats	10 cm	
Mats surface	horizontal, even, without gaps	
Extra soft landing mat at the vault	600 cm * 200 cm ; with lines	
2 extra soft landing mats at high bar	400 cm * 200 cm	

☐ Podium training

☐ Qualification round

☐ Final

☐ Team Final



Signature

Time & date

WAG - Apparatus Control Form A

(Forms B: see FIG Apparatus Norms Part IV)

II
WAG
01.01.2014
119

		APPARATUS CONTROL A - WAG GYMNASTICS		
Apparatus: WAG		Competition: Name of the Competition		Date:
Note: Measurements taken from the floor to the top of the apparatus				
Vaulting Table	Stipulation	Result - Action		
Height	125 cm +/- 1 cm measured 68cm from landing end			
Levers and knob covered				
Protection of anchor and floor supports under apparatus				
Protection for space between landing mat and vaulting table				
Safety collar: different color from carpet of spring board				
Enhanced color of round-off hand placement mat				
Uneven Parallel Bars	Stipulation	Result - Action		
Height of low bar	166 cm +/- 1 cm from under rail			
Height of high bar	246 cm +/- 1 cm from under rail			
Distance between bars	180 cm diagonal (maximum)			
Protection between bases and 2 m matting under UB				
Balance Beam	Stipulation	Result - Action		
Height of beam	125 cm +/- 1 cm			
Length of beam	500 cm			
Width of beam	10 cm			
Permanent coverings on ends				
Cushioning of the stands				
Floor	Stipulation	Result - Action		
Surface area	12x12m including delimitation line			
Elasticity of floor				
Chalk box for feet				
Springboards	Stipulation	Result - Action		
Height	20 cm +/- 1 cm, Cushion cover 2 cm +/- 0,05 = Total 22 cm +/- 1,5 cm			
1 hard and 1 soft board at the vault	hard board marked with a dot springs fixed			
1 soft board at the uneven parallel bars	springs fixed			
1 soft board at the beam	springs fixed			
Mats	Stipulation	Result - Action		
Height of all landing mats	20 cm +/- 1 cm			
Height of all extra soft landing mats	10 cm			
Mats surface	horizontal, even, without gaps			
Extra soft landing mat at the vault	600 cm * 200 cm; with lines			
Extra soft landing mat at the uneven parallel bars	400 cm * 200 cm			
Extra soft landing mat at the beam	400 cm * 200 cm			

☐ Podium training

☐ Qualification round

☐ Final

☐ Team Final

Signature

Time & date

TRA - Apparatus Control Form A

(Forms B: see FIG Apparatus Norms Part IV)

II
TRA
01.01.2014
120



APPARATUS CONTROL A - TRA GYMNASTICS

Competition
Logo

Competition: **Name of the Competition**

Apparatus: Trampoline	<input type="checkbox"/> Individual	<input type="checkbox"/> Synchro
------------------------------	-------------------------------------	----------------------------------

Trampoline	Stipulation	Result - Action
Height of the bed	115,5 cm +/- 0,5 cm (from the floor)	
Length of the bed	428 cm +/- 6 cm (under tension)	
Width of the bed	214 cm +/- 5 cm (under tension)	
Jumping zone	215 (+/- 4) x 108 (+/- 4) cm; cross: 70 (+/- 3) cm	
Bed construction	Web: 0,55 cm +/- 0,15 cm; max distance 1.6 cm Strings: 0,3 cm +/- 0,1 cm; max distance 1 cm	
Safety padding	Shock absorbing padding; thickness: 3,0-5,0 cm	
	The padding may not touch any part of the bed	
	The padding may extend over the bed by up to 3 cm	
	The bottom of the padding not to protrude above the level of the bed by more than 6 cm	
	Padding firmly fixed to the frame without hindering the normal action of the bed and springs	
Level	The frame and bed must be level	
Springs	Safely attached	
Area beneath	Construction: the competitor will not touch any part of the frame beneath the bed	
Safety platform mats	Stipulation	Result - Action
Width	300 cm +/- 2,5 cm	
Length	240 cm +/- 2,5 cm (including wedge, 40 cm)	
Thickness at bedside	7,5 cm +/- 0,5 cm	
Thickness at the end	20 cm +/- 2,0 cm	
Density		
Safety mats (on the floor)	Stipulation	Result - Action
Width	200 cm +/- 1 cm	
Height	Type a): 20 cm Type b): min. 20 cm	
Type	All mats must be of the same height and type	
Density		
Spotter mats	Stipulation	Result - Action
Material	Must be covered with a material which will slide easily	
Handles	Must be provided with at least 2 handles or one long handle on the two long sides of the mat	
Length	200 cm - 50 cm	
Width	150 cm - 50 cm	
Thickness	15 cm - 5 cm	
Density		

☐ Podium training

☐ Qualification round

☐ Team Final

Signature

Time & date

RG - Apparatus Control Form A

(Forms B: see FIG Apparatus Norms Part IV)

II
RG
01.01.2014
121



APPARATUS CONTROL A - RG GYMNASTICS


Competition
Logo

Competition: <i>Name of the Competition</i>	Date:
--	-------

RG1 Floor	Stipulation	Result - Action
Surface area	width A (1300 ± 3 cm)	
(delimiter lines belong to the competition area)	width B (1300 ± 3 cm)	
	diagonal A (1838 ± 5 cm)	
	diagonal B (1838 ± 5 cm)	
horizontal, even, without gaps		
Seams' direction	Towards Judges (Training: Towards Coaches)	
Border	horizontal (50cm); with slope (25-25cm)	
Safety zone	(200 cm)	
Delimitation strip	contrast, width (5 ± 0.5 cm)	
Minimum height of the hall	1000 - 1200 cm min	
RG10 Measurement Table	Stipulation	Result - Action
<u>suitable for measurement of diameter:</u>		
hoops	800 - 900 mm	
measurement of whole circle?		
balls	180 - 200 mm	
end of clubs	max. 30mm	
cane of ribbons	max. 10mm	
<u>suitable for measurement of lengths:</u>		
clubs	400 - 500 mm	
ribbons	5000mm Juniors (6000mm min. Seniors)	
doubled part of the ribbon	1000mm +/- 5 mm	
cane of ribbons	500 - 600 mm	
optional handle part of cane of ribbon	max. 100mm	
fixture of ribbons	70mm max.	
width of ribbons	40 - 60 mm	
<u>suitable balance:</u>		
precision	+/- 1g	
Hoops measurement	hanging position	
hoop / balls / clubs / ribbons without	min. 300 / 400 / 150 / 35 g (30g Juniors)	
Indication	all measures indicated unmistakably	

Signature

Time & date



6. Required Equipment for FIG - Competitions
MAG / WAG / RG / TRA

Competition Equipment for Men's Artistic Gymnastics (including training and warm-up hall)

II
MAG
01.01.2014
123

Competition Equipment for Men's Artistic Gymnastics

For World Championships and Olympic Games

		Quantity Arena	Quantity warm-up hall	Quantity for each training hall	Remarks
Floor Exercise					
Free exercise floor	MAG 1	1	1	1	
Magnesia stand for feet (filled with magnesite)		2	2	2	
Magnesia stand for hands (filled with magnesite)		1	1	1	
Supplementary mat 200x200x10 cm			2	2	
Pommel Horse					
Pommel horse (including anchoring system to the floor)	MAG 2	1	2	2	
Set of landing mats 10 cm, surface according to Apparatus Norms	MAG 12	1	2	2	
Magnesia stand for hands (filled with magnesite)		1	2	2	
Rings					
Ring frame	MAG 3	1	1	1	
Set of landing mats 20 cm, surface according to Apparatus Norms	MAG 11	1	1	1	
Ring hook		1	1	1	
Magnesia stand for hands (filled with magnesite)		1	1	1	
Hard foam block approx. 90 x 50 x 70 cm for preparation of the rings		1	1	1	
Supplementary mat 200x200x10 cm			1	1	
Vault					
Vaulting table (including anchoring system to the floor and 20 cm high padding of the feet)	MAG 4	1	1	1	
Runway with clear markage block at 25 meters		1	1	1	
Set of landing mats 20 cm, surface according to Apparatus Norms	MAG 11	1	1	1	
Supplementary mat 600x200x10 cm with marked landing area (two diverging lines and one central line)	MAG 13	1	1	1	Compulsory use
Soft crash mat 300x200x30 cm			1	1	
Vaulting board 'hard' (with fixed springs)	MAG 14	1	1	1	
Vaulting board 'soft' (with fixed springs)	MAG 14	1	1	1	
Vaulting board Safety Collar	MAG 15	1	1	1	Compulsory use with round-off vaults
Mat for hands 120x100x3 cm	MAG 16	1	1	1	Use not compulsory
Tape measure 25 meters		1	1	1	
Magnesia stand for feet (filled with magnesite)		1	1	1	
Magnesia stand for hands (filled with magnesite)		1	1	1	
Parallel Bars					
Parallel bars (if necessary with anchoring system to the floor / podium)	MAG 5	1	2	2	
Set of landing mats 20 cm, surface according to Apparatus Norms	MAG 11	1	2	2	
Vaulting board 'soft' (with fixed springs)	MAG 14	1	2	2	
Magnesia stand for hands (filled with magnesite)		1	2	2	
Supplementary mat 200x200x10 cm			2	2	
Horizontal Bar					
Horizontal bar (including anchoring system to the floor)	MAG 6	1	1	1	
Set of landing mats 20 cm, surface according to Apparatus Norms	MAG 11	1	1	1	
Supplementary mat 400x200x10 cm	MAG 13	2	2	2	Compulsory use
Magnesia stand for hands (filled with magnesite)		1	1	1	
Hard foam block, approx. 50x50x50 cm for preparation of rails		1	1	1	

Spare parts such as rails, vaulting boards, pommels etc. at the discretion of the Organiser

Please note that for all FIG sanctioned events the apparatuses shall have a valid FIG-certificate and the FIG must be informed in due time of the official apparatus manufacturer and the exact product. It is allowed to have more than one apparatus manufacturer but it must be guaranteed that exactly the same product is used in the training- warm-up- and competition hall.

Competition Equipment for Women's Artistic Gymnastics (including training and warm-up hall)

II
WAG
01.01.2014
124

Competition Equipment for Women's Artistic Gymnastics

For World Championships and Olympic Games

		Quantity Arena	Quantity warm-up hall	Quantity for each training hall	Remarks
Vault					
Vaulting table (including anchoring system to the floor and 20 cm high protection of the feet)	WAG 1	1	1	1	
Set of landing mats 20 cm, surface according to Apparatus Norms	WAG 11	1	1	1	
Runway with clear markage at 25 meters		1	1	1	
Supplementary mat 600x200x10 cm with marked landing area (two diverging lines and one central line)	WAG 13	1	1	1	Compulsory use
Soft crash mat 300x200x30 cm			1	1	
Vaulting board 'hard' (with fixed springs)	WAG 14	1	1	1	
Vaulting board 'soft' (with fixed springs)	WAG 14	1	1	1	
Vaulting board Safety Collar	WAG 15	1	1	1	Compulsory use with round-off vaults
Mat for hands 120x100x3 cm	WAG 16	1	1	1	Use not compulsory
Tape measure 25 meters		1	1	1	
Magnesia stand for feet (filled with magesia)		1	1	1	
Magnesia stand for hands (filled with magnesia)		1	1	1	
Uneven Bars					
Uneven bars	WAG 2	1	2	2	
10 cm support plates		1	1	1	
Set of landing mats 20 cm, surface according to Apparatus Norms	WAG 11	1	2	2	
Supplementary mat, 400x200x10 cm	WAG 13	1	2	2	compulsory use
Vaulting board 'soft' (with fixed springs)	WAG 14	1	2	2	
Magnesia stand for hands (filled with magesia)		1	2	2	
Hard foam block, approx. 50x50x50 cm for preparation of rails		1	2	2	
Balance Beam					
Balance beam with padded legs	WAG 3	1	2	2	All knobs and levers padded or removed
Set of landing mats 20 cm, surface according to Apparatus Norms	WAG 11	1	2	2	
Supplementary mat, 400x200x10 cm	WAG 13	1	2	2	Compulsory use
Vaulting board 'soft' (with fixed springs)	WAG 14	1	2	2	
Magnesia stand for hands (filled with magesia)		1	2	2	
Floor Exercise					
Free exercise floor	WAG 4	1	1	1	
Magnesia stand for feet (filled with magesia)		2	2	2	
Magnesia stand for hands (filled with magesia)		1	1	1	
Supplementary mat 200x200x10 cm			2	2	

Spare parts such as rails, vaulting board etc. at the discretion of the Organiser

Please note that for all FIG sanctioned events the apparatuses shall have a valid FIG-certificate and the FIG must be informed in due time of the official apparatus manufacturer and the exact product. It is allowed to have more than one apparatus manufacturer but it must be guaranteed that exactly the same product is used in the training- warm-up- and competition hall.

Competition Equipment for Rhythmic Gymnastics (including training and warm-up hall)

II
RG
01.04.2015
125

Competition Equipment for Rhythmic Gymnastics

For World Championships and Olympic Games

		Quantity Arena	Quantity warm-up hall	Quantity for each training hall *	Remarks
Rhythmic Gymnastics					
RG Floor	RG 1	1	max. 2		9 floors for OG 12 floors for World Championships 9 floors only for World Championships in the year following the Olympic Games
Minimum safety distance		2,5 m	0,5 m	0,5 m	
Acoustic separations between the floors			between the floors	between the floors	
Music devices		1	1 per floor	1 per floor	
Ballet Bar and mirror				1 per warm-up zone	
Device to iron ribbons			1	1	
Measurement Table for RG with balance	RG 10	-	1	-	

* = according to size of the hall

Please note that for all FIG sanctioned events the apparatuses shall have a valid FIG-certificate and the FIG must be informed in due time of the official apparatus manufacturer and the exact product. It is allowed to have more than one apparatus manufacturer but it must be guaranteed that exactly the same product is used in the training- warm-up- and competition hall.

Competition Equipment for Trampoline,
Double Minitrampoline, Tumbling
(including training and warm-up hall)

II
TRA
01.01.2014
126

For World Championships and Olympic Games

		Quantity Arena	Quantity warm-up hall	Quantity for each training hall **	Remarks
Trampoline					
Trampolines	TRA 1	4	4	4	
Safety platforms (see TRA 1, Art. 6)		8	8	8	
Platform mats with wedges (see TRA 1, Art. 6)		8	8	8	
Stability plates *		16	16	16	
Spotter mats (see TRA 1, Art. 7)	TRA 12	4	4	4	
Safety mats on the ground (see TRA 1, Art. 8)	TRA 11	30	30	30	30 mats if 300x200x20 cm
Time Measurement Device	TRA 15	2 sets	2 sets *	2 sets *	
Magnesia stands (filled with magnesia)		2	2	2	
Double Mini-Trampoline					
Double Mini-Trampoline	TRA 2	1	1	1	
Run-up (see TRA 2, Art. 4)		1	1	1	
Spotter-mat (see TRA 2, Art. 5)	TRA 12	1	1	1	
Landing mats with marking of landing zones (see TRA 2, Art. 3)	TRA 11	1	1	1	
Additional safety mat 300x200x20 cm (see TRA 2, Art. 3.2)		1	1	1	Placement: behind the landing area
Safety mats besides the DMT (see TRA 2, Art. 6)	TRA 11	2	2	2	
Set of Safety mats (min. 50 cm wide; 5 cm thickness) *		1	1	1	Placement: around the landing area
Magnesia stands (filled with magnesia)		1	1	1	
Tumbling					
Tumbling track	TRA 3	1	1	1	
Run-up (see TRA 3, Art. 3)		1	1	1	
Landing mats with marking of landing zone (see TRA 3, Art. 2)	TRA 11	1	1	1	
Supplementary mat 400x200x10 cm	TRA 13	1	1	1	With marking of landing zone
Additional safety mat 300x200x20 cm (see TRA 3, Art. 2.2)		1	1	1	Placement: behind the landing area
Vaulting board 'hard'	TRA 14	1	1	1	
Vaulting board 'soft'	TRA 14	1	1	1	
Set of Safety mats (min. 50 cm wide; 5 cm thickness) *		1	1	1	Placement: around the landing area
Magnesia stands (filled with magnesia)		1	1	1	

* = not compulsory

** = if applicable

Spare parts at the discretion of the Organiser

Please note that for all FIG sanctioned events the apparatuses shall have a valid FIG-certificate and the FIG must be informed in due time of the official apparatus manufacturer and the exact product. It is allowed to have more than one apparatus manufacturer but it must be guaranteed that exactly the same product is used in the training- warm-up- and competition hall.

PASTORELLI®



FIG OFFICIAL
PARTNER



Professional sportswear and equipment supplier
Rhythmic Gymnastics

www.pastorellisport.com



FÉDÉRATION INTERNATIONALE DE GYMNASTIQUE

III Certificates and diplomas

Advertising 11

Content

III
01.01.2014
1

	Page
1. Each apparatus must have a valid FIG Certificate	III/3
2. Validity of the Certificate	III/3
3. Rights of the Apparatus Manufacturer with a valid FIG Certificate	III/3
4. Procedure to obtain a Certificate	III/3
4.1 Practical Test	
4.2 Testing by an FIG recognised Testing Institute	
4.3 Recognition of the FIG Statutes, Rules and Regulations, Applicable law and arbitration, Code of Auto discipline	
4.4 Issuing of FIG Certificate	
5. Testing Fees of the FIG recognised Testing Institutes	III/5
6. Fee for the Certificates	III/5
7. Obtaining a certificate without testing for apparatus produced by another manufacturer	III/5
8. FIG Diploma	III/6
9. Reward for the suppliers of World Championships and World Cup Finals	III/6
10. Renewal of Certificates	III/6
11. New Apparatus, Modified Apparatus, New Developments	III/7
12. Publication of the FIG Certificates and Diplomas	III/7
13. FIG Sticker - FIG APPROVED	III/7
14. Control of apparatus at the competitions Re-testing of apparatus by the FIG at the Testing Institute	III/8
15. FIG recognised Testing Institutes	III/8
16. Publicity and manufacturer's logo on apparatus	III/9
17. Waiver of Liability	III/9
18. Current Fees for FIG-Certificates	III/9
19. Code of Auto discipline	III/9

Content

III
01.01.2014
2

Page

Appendix 1	Directives for the Use of Official FIG Designations and Logos	III/10
Appendix 2	FIG Recognised Testing Institutes Addresses and Contact Persons	III/14
Appendix 3	FIG Recognised Testing Institutes What can be tested where?	III/15
Appendix 4	Testing Fees of the FIG Recognised Testing Institutes	III/16
Appendix 5	Code of Auto discipline	III/18
Appendix 6	Intermediate Rules	III/26

III
01.01.2016
3

1. Each apparatus must have a valid FIG Certificate

The definition of «Apparatus» for these Apparatus Norms is:

All apparatus used at FIG competitions and listed in these Apparatus Norms.

Each apparatus, including all hand apparatus used in Rhythmic Gymnastics, must have its own, valid Certificate, to be used at FIG events, Olympic Games, World Games and international events.

For Olympic Games, World Championships, World Games and other multi-sports games (e.g. Commonwealth Games, Asian Games, Panam Games, University Games), the apparatus must have a valid certificate at least 1 year prior to the competitions. For all other competitions, the certificates must be valid at the latest at the moment of the invitation. Example: World Cup / World Series competitions: 3 months prior to the competitions.

2. Validity of the Certificate

The Certificates have a validity of two years. The expiry date is indicated on the certificate.

The FIG may, at any time, prolong or shorten the validity of issued Certificates or withdraw a Certificate.

3. Rights of the Apparatus Manufacturer with a valid FIG Certificate

When receiving a FIG Certificate, the apparatus manufacturer obtains the following rights:

- The right that the respective apparatus may be used at all official events of the FIG, its Continental Unions and member federations, as well as at the Olympic Games and World Games.
- The right to use the designation and the logo «FIG Approved» together in the catalogue and other publicity material, as prescribed in the respective directives of the FIG. (see Appendix 1)
- The use of the sticker « FIG Approved » on the respective apparatus.
- The regular publication in the list of certified apparatus in the FIG Bulletin and on FIG's website.
- One free advertisement (1 x ½ page, black and white) in the FIG Bulletin during the period of validity of each Certificate.

4. Procedure to obtain an FIG Certificate

The procedure has four steps:

- Practical test
- Testing at one of the FIG recognised Testing Institutes
- Declaration to be bound by the FIG's Statutes, Rules and Regulations as well as the provisions concerning governing law and arbitration
- Issuing of the Certificate by the FIG

III
01.01.2016
4

4.1 Practical Test

Apparatus manufacturers who wish a Certificate must first have their apparatus tested practically by gymnasts and coaches. For this purpose, the manufacturer contacts directly one of FIG's member federations, which can test the apparatus in a training centre by elite gymnasts. The apparatus must be tested under competition conditions. The manufacturer must provide a confirmation signed by a member federation containing the following:

«We confirm to have tested apparatus X under competition conditions at our training centre and/or at competitions. The apparatus is of the best quality, safe and suitable to be used at international competitions. We recommend that the FIG initiates the necessary procedures that this apparatus may be used at future international events. »

4.2 Testing by an FIG recognised Testing Institute

After the successful practical test by an FIG member federation, the apparatus must be announced at the FIG Secretary General to be tested by one of the FIG's recognised Testing Institutes. For contact persons and addresses see Appendix 2).

The Testing Institute informs the apparatus manufacturer and the FIG in writing, when the apparatus will be tested.

The Testing Institute tests the apparatus following the norms and testing procedures and prepares and submits a test report on behalf of the FIG and the apparatus manufacturer. Manufacturers can raise an objection against descriptions and dimensions of their equipment in the test report within a period of 2 weeks after receiving the report. All costs in connection with the testing (transport and testing fee) are the responsibility of the apparatus manufacturer and have to be paid prior to the tests. (Testing fees see Appendix 4).

For equipment with no existing test procedures the testing is done by the responsible Technical Committee after presentation of the confirmation according to 4.1. All costs are the responsibility of the apparatus manufacturer. The testing shall be announced to the FIG Secretary General.

4.3 Recognition of the FIG Statutes, Rules and Regulations

Applicable law and arbitration

Code of Auto discipline

Apparatus manufacturers who wish an FIG Certificate have to confirm in writing, that they recognise and strictly follow the FIG Statutes, Rules and Regulations. For their relationship with the FIG, the Testing Institutes, FIG's member federations, the Continental Unions and the organising committees, the apparatus manufacturer must accept to be governed by Swiss law and in case of disputes, to resolve such disputes to the exclusion of the ordinary courts by arbitration.

The following declaration must be made and signed:

«We herewith confirm unequivocally to respect and strictly follow the FIG Statutes, Technical Regulations, Code of Points, Apparatus Norms including the Code of Auto discipline and the Rules for Advertising and Publicity. This commitment is valid as long as we have a valid Certificate. »

III
01.01.2016
5

«All disputes arising out of or in connection with the Apparatus Norms, the testing and/or certification of our apparatus and in the relationship with the FIG, or one of their recognised Testing Institutes, Member Federations or Organising Committees shall be resolved, to the exclusion of the ordinary courts by an Arbitration Tribunal constituted in accordance with the Statutes and Regulations of the Court of Arbitration of Sport in Lausanne, Switzerland. We hereby undertake to comply with the said Statutes and Regulation, and to enforce in good faith the award to be rendered. The decision of the Arbitration Tribunal shall be final and binding on the parties.»

4.4 Issuing of FIG Certificates

The FIG Certificate will be issued by the Secretary General, provided the following conditions are met:

- The confirmation/recommendation from a member federation concerning the practical test (see 4.1).
- A positive test report from one of the FIG recognised Testing Institutes.
- Payment of the test fee and the Certificate fee.
- Confirmation / declaration from the manufacturer to recognise the FIG Statutes, Rules and Regulations and confirmation concerning applicable law and arbitration

5. Testing fees of the FIG recognised Testing Institutes

The testing fees must be approved by the FIG and must be identical at all FIG recognised Testing Institutes. The testing fees valid at this time are published in Appendix 4.

The Testing Institutes invoice the Apparatus Manufacturer directly with the testing fees and taxes and must be prepaid.

6. Fee for the Certificate

The fee to be paid to the FIG to obtain a Certificate and the attached rights are listed in Part III, § 18 and § 3.

This fee is decided by the Executive Committee and may be adjusted every two years if necessary.

This fee must be paid by the Apparatus Manufactures in advance to the FIG.

7. Obtaining a certificate without testing for apparatus produced by another manufacturer

Apparatus manufacturers and retailers may obtain an FIG certificate in their name to sell apparatus produced by another manufacturer according to the following conditions:

- Written approval from the apparatus manufacturer who has produced and tested his apparatus and has a valid certificate.
- Payment of the fee to the FIG for the requested certificate as per Art. 18 of Part III of the FIG Apparatus Norms
- The validity of the certificate cannot exceed the expiry of the original certificate of the manufacturer who has tested the apparatus

III
01.01.2016
6

- The manufacturer who produces the apparatus may withdraw his approval at any time with written notification to FIG

- The certificate cannot be extended without approval from the manufacturer who produces the apparatus

The description of the apparatus on the certificate must contain the name of the apparatus and an article number which is identical to the one listed in the catalogue. It must also bear the name of the manufacturer as well as the article number and name of the respective apparatus

8. FIG Diploma

Manufacturers, who are in possession of 12 or more valid Certificates, receive a FIG Diploma free of charge. The Diploma is valid as long as the manufacturer has 12 or more valid Certificates.

The FIG Diploma gives the apparatus manufacturer the following additional rights:

- The right to have two VIP accreditations to the official FIG Competitions
- The right to attend the FIG Congress, Council, Gala and Symposium
- The right to be a member of the FIG Apparatus Commission (3 partners at the time, rotation system)
- The right to bear the designation «Official FIG Partner» and to use this on his letter head and promotional material.
- The right, to use the FIG Logo on his letter head and catalogue. The directives (Appendix 1) must be followed.
- A free advertisement (1 x 1/1 page, in colour) in World of Gymnastics every second year.
- A free advertisement in the FIG Bulletin (1 x 1/1 page, black and white) every second year.
- To be mentioned in the list of the Official FIG Partners and official Sponsors, this is published in every Bulletin, in the Directory and on the FIG website.
- The publication of the manufacturer's logo in a composite page together with the official FIG sponsors in every issue of World of Gymnastics.
- A free advertisement (1/1 page, black and white) in the respective Code of Points

9. Reward for the suppliers of World Championships and World Cup Finals

Apparatus manufacturers who have supplied the apparatus for the World Championships or the World Cup Final alone or with a maximum of one other manufacturer may request a confirmation from the FIG as «Official Supplier of the «World Championships XXX» or of the «World Cup Final XXX». This confirmation may be used for publicity purposes, following the respective Directives of the FIG, (see Appendix .1)

10. Renewal of Certificates

After the first period of validity (2 years) a Certificate may be prolonged maximum twice for another period of two years by paying the fee without testing, provided the norms and/or testing procedures for the respective apparatus have not changed in the meantime and that the apparatus has not lead to any complaints during the validity of the Certificate.

III
01.01.2016
7

If the construction of the apparatus or the functional properties have changed, the apparatus has to undergo a practical test (see 4.1) as well as by a Testing Institute (see 4.2).

In case of small modifications which do not affect the functional properties or would not lead to a different test results, the FIG may dispense the apparatus manufacturer from testing. In cases of doubt, the Secretary General takes a final decision in consultation with the FIG Test Institute and the President of the Apparatus Commission.

To renew a certificate the apparatus manufacturer must send a request to the FIG – secretariat. This request must include the following three statements:

“We confirm that the construction of the apparatus and the functional properties have not changed since the last successful test!”

“We confirm that the materials used are the same and have the same functional properties as those used for the last successful test!”

“We confirm that our apparatus has been adapted to the apparatus norms valid today!”

The FIG may require a re-test or refuse the prolongation.

11. New Apparatus, Modified Apparatus, New Developments

Those are defined as follows:

- New apparatus which are not included in the Apparatus Norms
- Apparatus which are listed in the Apparatus Norms, but which have been significantly modified in their form, functional properties or development

Before the manufacturer constructs a prototype, the FIG recommends that the President of the Apparatus Commission and/or the respective TC President be contacted to find out if such a new apparatus is desired.

If this is confirmed, a prototype can be constructed and presented to the FIG.

Upon recommendation of the respective TC and the Apparatus Commission, the Executive Committee may decide on a general practical test. For such a test, the EC invites manufacturers to produce prototypes and to have those tested at the same time in 4-5 training centres chosen by the FIG. The costs are the responsibility of the apparatus manufacturers interested in the project. After analyses of the test results the Apparatus Commission - in cooperation with the respective TC and the other FIG Commissions - makes the necessary proposals to the EC for the further procedure regarding the possible introduction of the new apparatus.

12. Publication of the FIG Certificates and Diplomas

The FIG regularly publishes a list of the valid Certificates and Diplomas including the period of validity.

13. FIG Sticker «FIG APPROVED»

Apparatus manufacturers who are in possession of a valid FIG Certificate have the right to stick or print the « FIG Approved » sticker on the respective apparatus. The sticker can be received from the FIG free of charge. «FIG Approved» is also available by electronic support. For colours and size see Appendix 1.

Upon written approval by the FG Secretary General, the Sticker “FIG-Approved” can also be used for apparatuses which have no certificate and where no test is required i.e. supplementary mats, spotter mats, measuring table for RG-Apparatus etc. The written approval of the Secretary General also allows the manufacturer to use the term “FIG-Approved” for the publicity and offers of the above mentioned kind of apparatuses.

III
01.01.2016
8

Each written approval issued by the Secretary General is valid for two years and costs 25% of the current fees for FIG Certificates as per point III, p. 18 of these regulations per apparatus.

These written approvals cannot be considered as a "certificate" in the spirit of these rules.

It is not possible to issue such an approval for manufacturers who have no valid certificate.

14. Control of Apparatus at the competitions **Re-testing of apparatus by the FIG at the Testing Institute**

At the official events of the FIG, as well as at the Olympic Games and World Games, the apparatus are officially controlled on site. This control mainly consists of checking the measurements, making sure that the apparatus used at the competition is identical to the tested one, as well as a control of the layout, safety area and matting. The apparatus manufacturer is responsible that those delivered apparatus are 100% identical to the one tested in respect of the material used as well as the construction. The apparatus manufacturers are fully responsible that the norms are strictly respected; the correct setting up of the apparatus is the responsibility of the organising committee. The FIG has and reserves the right to re-test apparatus before, during and after an event at the nearest recognised Testing Institute. In case the testing report is positive, all costs are at the charge of the FIG. In case the report is negative, the costs are at the charge of the apparatus manufacturer. Furthermore the validity of the Certificate is immediately withdrawn. The Disciplinary Commission decides about the duration of a ban against the respective manufacturer. Afterwards, the manufacturer may apply Certificate to be issued by the FIG (following 4.4).

15. FIG recognised Testing Institutes

The following Testing Institutes are recognised by the FIG at this time:

- Albert Ludwigs' University of Freiburg (GER)
- Tokyo Institute of Technology (JPN)

For addresses, contact person, delivery addresses etc. see Appendix 1

All Testing Institutes charge the same testing fee. (See Appendix 4)

The testing fees must be approved by the FIG.

The Testing Institutes are absolutely neutral and must strictly follow the FIG testing procedures. Testing equipment and conditions must be equal at all Testing Institutes.

It is the goal that all Testing Institutes are able to test all apparatus.

Appendix 3 lists which institute can test which apparatus.

Part IV of the Apparatus Norms also gives the necessary information about how many apparatus, m2 or m of the respective apparatus must be supplied for testing purposes.

16. Publicity and apparatus manufacturer's logo on the apparatus

See FIG Rules for Advertising and Publicity.

III
01.01.2016
9

17. Waiver of Liability

With these Apparatus Norms, the FIG and its member federations, as well as the Testing Institutes are in no way responsible for the apparatus. The FIG, its member federations and the Testing Institutes waive all liability in connection with the use of apparatus described in these Apparatus Norms.

18. Current Fees for FIG Certificates

The following fees for Certificates are applied:

The fee to be paid to issue a Certificate for the first time or to renew a Certificate depends on the number of valid Certificates a manufacturer already has

Number of Certificates held	Fee in EURO per Certificate
1	5'000
2 - 3	4'000
4 - 5	3'000
6 - 7	2'000
8 - 9	1'000
10 - 11	800
12 and more	600

19. Code of Auto discipline

A "Code of Auto discipline" has been elaborated by the Apparatus Commission and approved by the FIG Executive Committee in order to determine the rules, concerning the manufactures relations with the FIG and between themselves.

The rules envisaged in the Auto discipline Code are applied automatically to each infraction of the Apparatus Norms in force.

See Appendix 5

III
01.01.2006
10

DIRECTIVES / REGULATIONS FOR THE USE OF OFFICIAL FIG DESIGNATIONS AND LOGOS

1. GENERAL PRINCIPLES

- 1.1. The designations and logotypes/logos which are presented in this document are property of the *Fédération Internationale de Gymnastique (FIG)*. Their use requires the FIG's authorization. Any illegal use or non-conformity with these directives will be prosecuted and results in the withdrawal of the certificate or diploma.
- 1.2. The **acquisition** conditions for these designations which are reserved for the FIG partners are included in the brochure "Apparatus Norms" published by the FIG.
- 1.3. The **use** of these designations and logotypes/logos which are reserved for the FIG partners is prescribed in this appendix.
- 1.4. The general graphic prescriptions are defined in the FIG Graphics Chart.
- 1.5. The graphic prescriptions reserved for the use of the FIG apparatus manufacturers are included in this appendix.
- 1.6. The use of any designation or logotype/logos other than those mentioned in this appendix is strictly prohibited.
- 1.7. Any other reference to "FIG", use of the abbreviation "FIG" (or "Fédération Internationale de Gymnastique" in any language) as well as wordings such as "following FIG Norms", "in the process to be tested" etc. are strictly prohibited.

2. DEFINITIONS

These directives regulate the different rights of the three apparatus manufacturer categories as follows:

- 2.1. Holder of the **"FIG-Certificate"**
- 2.2. Holder of the **"FIG-Diploma"**
- 2.3. Holder of an FIG confirmation as
"Official Supplier of the World Championships" or as
"Official Supplier of the World Cup Final"

3. HOLDER OF THE FIG-CERTIFICATE

The holder of the" FIG Certificate" may use the logotype "**FIG Approved**" respecting the following conditions:

- 3.1. The logotype may only and exclusively be associated with only one element respectively one single article, apparatus or accessory duly certified by the FIG.
- 3.2. It may be used on an article respectively an apparatus or an accessory itself or it may be integrated in any type of advertising or publicity but only **in direct connection or relation** with the respective certified apparatus. The logotype may also appear in a description of the certified apparatus (advertisement, publicity leaflet etc.)
- 3.3. **It may not be used as an isolated element, separate from the apparatus.**
- 3.4. Consequently it may not appear on letter heads, cover pages of catalogues, or in editorial articles with advertising purposes, nor in any other institutional documents containing general information.
- 3.5. **Graphics**

3.5.1. Logotype FIG Approved: (respect the size as per 3.6.1)



3.5.2. Colours

According to the range defined by the FIG Graphics Chart.

- **Black**
- **Blue Pantone 3005 U**
- **Red Warm red CV**

3.6. Use and size / Maximum dimensions

3.6.1. On printed matters

Formats:	A5	14.8 x 21.0 cm	ø 08 mm max.
	A4	21.0 x 29.7 cm	ø 12 mm max.
	A3	29.7 x 42.0 cm	ø 18 mm max.
	A2	42.0 x 59.4 cm	ø 35 mm max.
	A1	59.4 x 84.1 cm	ø 60 mm max.

III
01.01.2006
12

3.6.2. On the apparatus

The logotype "**FIG Approved**" may only be applied to the support surfaces (supports, legs of apparatus) of the apparatus. Maximum diameter is 35 mm.

On the floor and on the mats the logotype may appear in one of the four corners with a maximum distance of 5 cm to the corner or on the side of the floor/mat with the exception of the surfaces which are reserved for advertising purposes as defined in the "FIG Rules for Advertising and Publicity ". Maximum diameter is 35 mm.

On the apparatus for rhythmic gymnastics the logotype/sticker "**FIG Approved**" is described in RG, 2, 3, 4, 5 and 6, pages 71/72 in chapter II of the FIG Apparatus Norms.

4. HOLDER OF THE FIG DIPLOMA

- 4.1. The right to use the designation "**Official FIG Partner**" subject to article 1.5 of the "FIG Rules for Advertising and Publicity".
- 4.2. The right to use the **FIG Logo** for advertising purposes only, strictly respecting the FIG Graphics Chart.

In addition to the rights listed in chapter 3, the holder of a FIG Diploma obtains:

FIG Logo:



- 4.3. The title "Official FIG Partner" and the FIG logotype may by no means be used directly attached to or with a product but only with the **company name or identity** of the holder of the FIG Diploma. (e.g.: letter heads, envelopes, cover pages of catalogues, various kinds of printed material, newsletters, "give aways" etc.)

Appendix 1

III
01.01.2006
13

5. HOLDER OF AN FIG CONFIRMATION AS "OFFICIAL SUPPLIER FOR THE WORLD CHAMPIONSHIPS" OR AS "OFFICIAL SUPPLIER OF THE WORLD CUP FINAL"

- 5.1. The apparatus manufacturer who has been duly confirmed by the FIG may use the designation

"Official Supplier of the World Championships X"
"Official Supplier of the World Cup Final Y"

- 5.2. The use of the above-mentioned designation (for advertising purposes only) can only be associated with the supplied apparatus and also with the company name of the manufacturer. (e.g.: letter heads, envelopes, cover pages of catalogues, various kinds of printed material, newsletters, "give aways" etc.)

- 5.3. The above-mentioned designation may be used together with the FIG logotype according to the regulations of the FIG Graphics Chart and within the following dimensions:

5.4.	<u>Formats:</u>	A5	14.8 x 21.0 cm	Ø 8 mm max.
		A4	21.0 x 29.7 cm	Ø 12 mm max.
		A3	29.7 x 42.0 cm	Ø 18 mm max.
		A2	42.0 x 59.4 cm	Ø 35 mm max.
		A1	59.4 x 84.1 cm	Ø 60 mm max.

RECOMMENDATION

We strongly recommend that the holder of a certificate or a diploma should send his drafts of all printed matters to the FIG to be proof-read prior to printing.

III
01.01.2006
14

FIG RECOGNISED TESTING INSTITUTES**ADDRESSES AND CONTACT PERSONS****Albert Ludwigs University**

Institute of Sport and Sport Science - GYMLAB
Schwarzwaldstrasse 175
D-79117 Freiburg i. Br.
Germany

Phone +49 761 203 4554
e-mail ludwig.schweizer@sport.uni-freiburg.de

Contact Person Ludwig Schweizer

Tokyo Institute of Technology

Faculty of Engineering
Department of Architecture and Building Engineering
FIG Norm Testing Laboratory (Ono Lab.)
2-12-1 O-okayama
Meguro-ku
Tokyo 152-8552
Japan

Fax +81 3 5734 3164
Phone +81 3 5734 3164
E-mail mikami@mei.titech.ac.jp

Contact Person Takamasa Mikami

FIG RECOGNISED TESTING INSTITUTES

- What can be tested where? -

III
01.01.2011
15

MAG	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Floor	MAG1	Complete Test	√	√
	Pommel Horse	MAG2	Complete Test	√	√
		MAG2-1	Shock Absorption	√	√
		MAG2-2	Top Friction of Horse Body	√	√
		MAG2-3	*Pos. Stability of Pommels	√	√
		MAG2-4	Friction of Pommels	√	√
	Rings	MAG3	Complete Test	√	√
	Vaulting Table	MAG4	Complete Test	√	√
	Parallel Bars	MAG5	Complete Test	√	√
		MAG5-1	Static traction stress	√	√
		MAG5-2	Stress by pendulum swing	√	√
		MAG5-3	Oscillation damping	√	√
		MAG5-4	Lateral stability	√	√
	Horizontal bar	MAG6	Complete Test	√	√
		MAG6-1	Static traction stress	√	√
		MAG6-2	Stress by pendulum swing	√	√
		MAG6-3	Oscillation damping	√	√
	Landing Mat 20cm	MAG11	Complete Test	√	√
	Landing Mat 10cm	MAG12	Complete Test	√	√
	Vaulting Board	MAG14	Complete Test	√	√
WAG	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Vaulting Table	WAG1	Complete Test (see MAG4)	√	√
	Uneven Bars	WAG2	Complete Test	√	√
		WAG2-1	Static traction stress	√	√
		WAG2-2	Stress by pendulum swing	√	√
		WAG2-3	Oscillation damping	√	√
	Balance Beam	WAG3	Complete Test	√	√
		WAG3-1	Shock Absorption	√	√
		WAG3-2	Top Friction	√	√
	Floor	WAG4	Complete Test (see MAG1)	√	√
	Landing Mat 20cm	WAG11	Complete Test (see MAG11)	√	√
	Vaulting Board	WAG14	Complete Test (see MAG14)	√	√
RG	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Floor	RG1	Complete Test	√	√
		RG1-1	Shock Absorption	√	√
		RG1-2	Static stiffness	√	√
		RG1-3	Top Friction	√	
AER	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Floor	AER1	Complete Test	√	√
	Aerobic Step	AER2	Complete Test	√	
TRA	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Trampoline	TRA1	Complete Test	√	
	Tumbling Track	TRA3	Complete Test	√	
		TRA3-1	Shock Absorption	√	
		TRA3-2	Top Friction	√	
	Landing Mat 20cm	TRA11	Complete Test	√	√
	Vaulting Board	TRA14	Complete Test (see MAG14)	√	√
	TMD	TRA15	Complete Test	√	
ACRO	Apparatus	Code	Test Procedure	Frbg	Tokyo
	Floor	ACRO1	Complete Test (see MAG1)	√	√
	Landing Mat 20cm	ACRO11	Complete Test (see MAG11)	√	√

**TESTING FEES OF THE FIG
RECOGNISED TESTING INSTITUTES**

III
01.01.2014
16

MAG	Apparatus	Code	Test Procedure	Charge
	Floor	MAG1		€ 4000.-
	Pommel Horse	MAG2	Complete Test	€ 3600.-
		MAG2-1	<i>Shock Absorption</i>	€ 2000.-
		MAG2-2	<i>Top Friction of Horse Body</i>	€ 600.-
		MAG2-3	<i>Pos. Stability of Pommels</i>	€ 400.-
		MAG2-4	<i>Friction of Pommels</i>	€ 600.-
	Rings	MAG3		€ 2000.-
	Vaulting Table	MAG4		€ 3600.-
	Parallel Bars	MAG5	Complete Test	€ 5200.-
		MAG5-1	<i>Static traction stress</i>	€ 600.-
		MAG5-2	<i>Stress by pendulum swing</i>	€ 2000.-
		MAG5-3	<i>Oscillation damping</i>	€ 2000.-
		MAG5-4	<i>Lateral stability</i>	€ 600.-
	Horizontal Bar	MAG6	Complete Test	€ 5700.-
		MAG6-1	<i>Static traction stress</i>	€ 600.-
		MAG6-2	<i>Stress by pendulum swing</i>	€ 3400.-
		MAG6-3	<i>Oscillation damping</i>	€ 1700.-
	Landing Mat 20cm	MAG11		€ 2000.-
	Landing Mat 10cm	MAG12		€ 2000.-
	Vaulting Board	MAG14		€ 3000.-
WAG	Apparatus	Code	Test Procedure	Charge
	Vaulting Table	WAG1		See MAG4
	Uneven Bars	WAG2	Complete Test	€ 6800.-
		WAG2-1	<i>Static traction stress</i>	€ 800.-
		WAG2-2	<i>Stress by pendulum swing</i>	€ 4000.-
		WAG2-3	<i>Oscillation damping</i>	€ 2000.-
	Balance Beam	WAG3	Complete Test	€ 2600.-
		WAG3-1	<i>Shock Absorption</i>	€ 2000.-
		WAG3-2	<i>Top Friction</i>	€ 600.-
	Floor	WAG4		See MAG1
	Landing Mat 20cm	WAG11		See MAG11
	Vaulting Board	WAG14		See MAG14
RG	Apparatus	Code	Test Procedure	Charge
	Floor	RG1	Complete Test	€ 4000.-
		RG1-1	<i>Shock Absorption</i>	€ 2000.-
		RG1-2	<i>Static stiffness</i>	€ 400.-
		RG1-3	<i>Top Friction</i>	€ 1600.-
AER	Apparatus	Code	Test Procedure	Charge
	Floor	AER1		€ 2000.-
	Aerobic Step	AER2		€ 500.-
TRA	Apparatus	Code	Test Procedure	Charge
	Trampoline	TRA1		€ 4000.-
			Spring test (1 Spring)	€ 250.-
	Tumbling Track	TRA3	Complete Test	€ 3400.-
		TRA3-1	<i>Shock Absorption</i>	€ 2400.-
		TRA3-2	<i>Top Friction</i>	€ 1000.-
	Landing Mat 20cm	TRA11		See MAG11
	Vaulting Board	TRA14		See MAG14
	TMD	TRA15	Complete Test	€ 2000.-
ACRO	Apparatus	Code	Test Procedure	Charge
	Floor	ACRO1		See MAG1
	Landing Mat 20cm	ACRO11		See MAG11

Fees without additional Value added tax according to the Country of Test (actually: Germany 19%)

SERIOUS EQUIPMENT

FOR SERIOUS GYMNASTS

FIG Approved. Latest Technology.
Rebound Anchored.
SLIP RESISTANT. Smooth
and effortless. **Easy
Adjustments.**



ELITE™ ARTISTIC
VAULT TABLE

AAI® Find out more about AAI® equipment at
americanathletic.com/serious

CONNECT WITH US   

**TESTING FEES OF THE FIG
RECOGNISED TESTING INSTITUTES**

III
01.01.2014
17

Firms can obtain a discount on the testing fees provided that they own 4 or more certificates from the FIG. The percentage of discount depends on the number of certificates:

Number of Certificates	Discount
4 - 5	10%
6 - 7	20%
8 - 9	30%
10 - 11	40%
12+	50%

III
21.05.2009
18

I. General

- The present code has been elaborated by the Apparatus Commission and approved by the FIG Executive Committee in order to determine the rules, concerning the manufactures relations with the FIG and between themselves. The following should also be taken into account: The Technical Regulations, the manual «FIG Apparatus Norm, Part I-IV», the Code of Ethics and the Advertising and Publicity Rules.
- The rules envisaged in the Auto discipline Code are applied automatically to each infraction of the rules in force. Modifications to the present code may only be made by the FIG Executive Committee, upon request of the TCs, the Apparatus Commission or the FIG Partners.

II. Rules and Criteria for Partners

- Partners must have 12 different FIG Certificates.
- Supplied at least one official FIG World or Continental Championships.
- Elaborate a research program for the development and security of apparatus
- Contribute to the development of gymnastics in the world
- Ensure the financial health of company.

III. The Rights of the FIG Partners

- The right to have two VIP accreditations to the official FIG Competitions.
- The right to assist at the FIG Congress, Council, Gala and Symposium
- The right to be a member of the FIG Apparatus Commission (2 partners at the time, rotation system)
- The right to bear the designation «Official FIG Partner» and to use this on his letter head and promotional material.
- The right, to use the FIG Logo on his letter head and catalogue. The directives (Appendix 1) must be followed.
- A free advertisement (1 x 1/1 page, in colour) in World of Gymnastics every second year.
- A free advertisement in the FIG Bulletin (1 x 1/1 page, black and white) every second year.
- To be mentioned in the list of the Official FIG Partners and official Sponsors, this is published in every Bulletin, in the Directory and on the FIG website.
- The publication of the manufacturer's logo in a composite page together with the official FIG sponsors in every issue of World of Gymnastics.
- A free advertisement (1/1 page, black and white) in the respective Code of Points

IV. List of possible infractions against the FIG Apparatus Norms and Other FIG Rules and Regulations and Sanctions applied by the FIG**General Infractions:**

- Selling and/or offering certified apparatus without a valid certificate (certificate expired) (1st offence)
Written warning +

III
21.05.2009
19

- Rectify the offer (notification of the customer(s) by the manufacturer with copy to the FIG +
Fine of Euro 2,000.-*
- Same as above but 2nd offence.
*Rectify the offer (notification of the customer by FIG) +
Fine of Euro 5,000.-*
 - Selling and/or offering certified apparatus without a valid certificate (certificate not yet or never issued)
*Written warning +
Rectify his offer (notification of the customer(s) with copy to FIG)+
FIG may inform client(s) +
Fine of Euro 2,000. - +
Publication of the sanction*
 - Same as above, but 2nd offence.
*Written warning +
Rectify his offer (notification of the customer(s)+
FIG informs client(s) +
Fine of Euro 5,000. - +
Publication of the sanction +
If FIG Partner, loss of status for 1 year*
 - Testing an apparatus and selling and/or deliberately offering a different apparatus or construction or modified apparatus than the tested prototype.
*Withdrawal of the respective certificate for 1 year +
New test required +
Fine of Euro 5'000.- +
Publication of the sanction.*
 - Same as above, but 2nd offence.
*Withdrawal of certificates for 2 years +
New tests required +
Fine of Euro 10,000.- +
Publication of the sanction.*
 - Wrong statements to FIG concerning "unchanged" equipment
*Withdrawal of the respective certificate for one year +
New test required +
Fine of Euro 5,000.- +
Publication of the sanction.*
 - Same as above, but 2nd offence.
*Withdrawal of certificates for 3 years +
New tests required +
Fine of Euro 10,000.- +
Publication of the sanction.*

III
21.05.2009
20

Infractions committed at FIG events

- Selling, renting, sponsoring, offering, delivering, installing etc, not certified apparatus (not certified at all, expired certificate or different apparatus from the tested one) for use at an FIG event and events where FIG Certified equipment is requested.
Immediate rectification whenever possible +
Withdrawal of the respective certificate for one year +
New test required +
Fine of Euro 3,000.- +
Publication of the sanction.
- Same as above but 2nd offence.
Immediate rectification whenever possible +
Withdrawal of certificates for 2 years +
New tests required +
Fine of Euro 6,000.- +
Publication of the sanction.
- Lack of quality of apparatus used at FIG events
FIG may take the apparatus and send it for testing
- Lack of quality of apparatus used at FIG events (Apparatus does not pass the test after an event)
Withdrawal of the respective certificate for one year +
New test required +
Fine of Euro 2,000.- +
Publication of the sanction.
- Same as above but 2nd offence
Withdrawal of the respective certificate for 2 years +
New test required +
Fine of Euro 5,000.- +
Publication of the sanction.
- Infraction against size of Manufacturers Logo and/or Advertising on apparatus
Immediate rectification +
Written warning
- Same as above but 2nd offence
Immediate rectification +
Written warning +
Fine of Euro 500.-
- Infraction against placement of Manufacturers Logo on apparatus
Immediate rectification +
Written warning
- Same as above but 2nd offence
Immediate rectification +
Written warning +
Fine of Euro 500.-

Code of Auto discipline

III
21.05.2009
21

- Repeated infractions against size and / or placement of Manufacturers Logo (3rd and more cases)
Immediate rectification +
Fine of Euro 5,000.-
- Placement of Manufacturers Logo or anything else in the Advertising Area.
Immediate rectification +
Written warning
- Same as above but 2nd offence
Immediate rectification +
Written warning +
Fine of Euro 1,000.-
- Distribution of presents, PR, or other advertising and publicity items to competitors and or officials (FIG or Member Federations) without written approval of FIG at FIG events.
Immediate stop of action +
Written warning
- Same as above but 2nd offence
Immediate stop of action +
Written warning +
Fine of Euro 2,000.-
- Placing of advertising and publicity in the competition hall other than the standard advertising boards as foreseen in the Rules for Advertising and Publicity without the written approval of FIG
Immediate stop of action and rectification +
Written warning
- Same as above but 2nd offence
Immediate stop of action and rectification +
Written warning +
Fine of Euro 1,000.-
- Other infractions against the Rules for Advertising and Publicity
Similar sanctions as mentioned above, depending on the severity of the infraction.

Catalogues / Publicity / Flyers / Printed Matters / Advertising etc.

- Using the abbreviation FIG in any way for not FIG certified apparatus, suggesting or giving the wrong impression of a relationship with FIG.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
FIG may notify customer(s) +
Written warning
- Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers
With copy to the FIG +
Written warning +
FIG to notify customers +
Fine of Euro 5,000.-

III
21.05.2009
22

- Using the FIG logo without being an FIG partner
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning
- Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning +
Fine of Euro 5,000.-
- Using the logo "FIG Approved" for not certified apparatus.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning
- Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning +
Fine of Euro 5,000.-
- Not respecting the size of the FIG logo or FIG Approved logo.
Immediate stop of action and rectification +
Written warning
- Same as above, but 2nd offence.
Immediate stop of action and rectification+
Written warning+
Fine of Euro 500.-
- Repeated offence as mentioned above.
(3 and more cases)
Immediate stop of action and rectification+
Written warning +
Fine of Euro 2,000.--
- Not using the FIG Approved logo directly attached to the respective product, thus giving the impression that other not certified products could also be FIG Approved.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning
- Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning +
Fine of Euro 5,000.-
- Infractions of clients (retailers) of an FIG Manufacturer or FIG Partner misusing the word FIG, the FIG Logo or the logo FIG Approved

III
21.05.2009
23

- Immediate stop of action, rectification and notification of the customers with copy to the FIG +*
Written warning +
FIG informs the FIG Manufacturer
- Same as above, but 2nd offence or not following FIG's requests at the time of the 1st Offence,
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning+
Fine of Euro 1,000.- +
FIG requests FIG Manufacturer to no longer sell their products to the respective client.
Manufacturer's Certificate will be withdrawn by FIG if the problem remains.
 - Giving the impression of FIG approval or certification by using misleading wording such as e.g. "meets FIG specs", or "following FIG rules" or similar.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning
 - Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning +
Fine of Euro 1,000.-
 - Reference to "old" and/or no longer valid certificates or former Diplomas
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning
 - Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
Written warning +
Fine of Euro 5'000.- +
Possible withdrawal of other certificates
 - Using falsified certificates
Immediate stop of action, rectification and notification of the customers with copy to the FIG +
FIG may inform customer(s)
Fine of Euro 10,000.-
Publication of the sanction
 - Same as above, but 2nd offence.
Immediate stop of action, rectification and notification of the customers +
Fine of Euro 20,000.- +
Withdrawal of all Certificates for a time to be defined by FIG.
Publication of the sanction

III
21.05.2009
24

- NOT FOLLOWING OR RESPECTING SANCTIONS
Action and further sanctions to be taken at the discretion of FIG.
- Infractions not listed above
The FIG will take action and sanctions as deemed necessary at its discretion, following in principle similar cases listed above

In addition to all the fines and sanctions listed above, the FIG reserves the right to take additional action as deemed necessary.

V. Procedure in case of Infractions and Sanctions

Infractions may be observed by all concerned (Apparatus Manufacturers, FIG Officials and third parties). Such observations must be given in writing to the FIG Secretary General.

The Secretary General will then take the necessary actions.

Written warnings are treated and decided by the Secretary General.

Immediate actions and decisions for infractions committed during FIG events are taken by the Secretary General and in his absence by his representative or the President of the Superior Jury. If he deems necessary, he will then forward the case to the FIG Disciplinary Commission for further action.

The Secretary General will report all warnings to the Apparatus Commission.

Offences with fines are treated by the FIG Disciplinary Commission.

The FIG Secretary General will keep a list of all offences warnings and sanctions. This list will include the date of the offence.

The 1st offences will be considered as deleted after the following time period:

- Written warnings and offences with up to and including Euro 1,000.- after 1 Olympic Cycle.
- Offences with fines up to and including Euro 5,000.- after 2 Olympic cycles
- Offences with fines over Euro 5,000.- after 3 Olympic cycles

All fines will be credited to the FIG Development Fund.

VI. Appeal against Sanctions

- Warnings decided by the FIG Secretary General:

The Apparatus Manufacturers may make an appeal against decisions of the Secretary General to the FIG Disciplinary Commission.

No further appeal is possible. The decision of the FIG Disciplinary Commission is final.

- Decisions taken by the FIG Secretary General for concerning infractions during an FIG event:

III
21.05.2009
25

The Apparatus Manufacturers may make an appeal against decisions and actions taken by of the Secretary General to the Jury of Appeal of the respective competition.

No further appeal is possible. The decision of the Jury of Appeal is final.

- Sanctions decided by the FIG Disciplinary Commission

The Apparatus Manufacturers may make an appeal against the decision taken by the FIG Disciplinary Commission as follows:

instance of appeal: FIG Appeal Tribunal

Appeals must be made in writing within 21 days and sent to the President of the instance concerned with a copy to the FIG Secretary General.

Depending on the outcome of the appeal, the Disciplinary Commission and the Appeal Tribunal will decide who has to bear the costs.

The procedures and costs for appeals to the Disciplinary Commission and the FIG Appeal Tribunal are ruled in the FIG Code of Discipline.

VII. Rules for the distribution of the Letter of Recognition

- FIG Letter of Recognition to be given to the official manufactures for the excellence of their work.
- A special FIG diploma will be given to the official supplier of 3 World Championships or World Cup Finals in 2 Olympic cycles.
- A special recognition FIG plate is to be attributed for service rendered to the development of gymnastics in the capacity of FIG partner and for the good relations with the other manufactures.

Appendix 6
Intermediate Rules

III
01.01.2014
26

Intermediate Rules re.

Impressum

Edition 2017:

Publisher	Fédération Internationale de Gymnastique
Responsible	<u>FIG - Apparatus Commission</u>
Drawings	Karl - Heinz Schwirtz / Ludwig Schweizer
Translations	FIG Secretariat / GYMLAB – University of Freiburg
©	Fédération Internationale de Gymnastique

Elegance is an attitude

dyg

Yana Kudryavtseva

LONGINES



OFFICIAL TIMEKEEPER



Longines DolceVita